

TC12K120

Telecentric lens for 12k and 16k linescan cameras, magnification 0.529 x, M72 x 0.75 mount

SPECIFICATIONS

Magnification	(x)	0.529
Image circle Ø	(mm)	62.4

Object field of view

with line - 12k detector 12k x 5.2 µm	(mm)	117.9
with line - 12k detector 12k x 5 µm	(mm)	116.1
with line - 16k detector 16k x 3.5 µm	(mm)	108.4
with line - 8k detector 8k x 7.5 µm	(mm)	108.4

Optical specifications

Working distance (1)	(mm)	254.0
wF/# (2)		16
Telecentricity typical (max) (3)	(deg)	< 0.06 (0.08)
Distortion typical (max) (4)	(%)	< 0.06 (0.08)
Field depth (5)	(mm)	4
CTF@ 70 lp/mm	(%)	> 40

Mechanical specifications

Length (6)	(mm)	722.1
Diameter	(mm)	180
Mass	(g)	8000
Mount (7)		M72x0.75 FD6.56

Last update: 2019-06-17

NOTES

- Working distance: distance between the front lens and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request
- Maximum slope of principal rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a very sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 7 µm.
- Indicates the availability of an integrated camera phase adjustment feature.
- Measured from the front end of the mechanics to the camera flange.
- FD stands for Flange Distance (in mm), defined as the distance from the mounting flange (the "metal ring" in rear part of the lens) to the camera detector plane.

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators

LTCLHP120-R	Telecentric HP illuminator, beam diameter 150 mm, red
LTCLHP120-G	Telecentric HP illuminator, beam diameter 150 mm, green
LTCLHP120-W	Telecentric HP illuminator, beam diameter 150 mm, white



LTLADC series



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

Continuous LED low angle direct ringlights

LTZZO170-75-3-W24V	LED low angle ringlight, 3 LED rows, outer diameter 175 mm, 75°, white, 24V
LTZZO170-75-3-R-24V	LED low angle ringlight, 3 LED rows, outer diameter 175 mm, 75°, red, 24V
LTZZO170-75-3-G-24V	LED low angle ringlight, 3 LED rows, outer diameter 175 mm, 75°, green, 24V
LTZZO170-75-3-B-24V	LED low angle ringlight, 3 LED rows, outer diameter 175 mm, 75°, blue, 24V



LTRNST series

LED ring illuminators - straight type

LTRN120RD	Ring LED illuminator, inner diameter 180 mm, straight type, red 630 nm
LTRN120GR	Ring LED illuminator, inner diameter 180 mm, straight type, green 525 nm
LTRN120BL	Ring LED illuminator, inner diameter 180 mm, straight type, blue 470 nm
LTRN120NW	Ring LED illuminator, inner diameter 180 mm, straight type, white



LTBRDC series

Continuous LED bar lights

LTZPFL160-00-6-W-24V	LED bar light, 6 LED rows, 160X26.3 illumination area, white, 24V
LTZPFL160-00-6-R-24V	LED bar light, 6 LED rows, 160X26.3 illumination area, red, 24V
LTZPFL160-00-6-G-24V	LED bar light, 6 LED rows, 160X26.3 illumination area, green, 24V
LTZPFL160-00-6-B-24V	LED bar light, 6 LED rows, 160X26.3 illumination area, blue, 24V



LTLNC series

Continuous LED line lights

LTLNC100-W	LED line light 100 mm, white
LTLNC100-R	LED line light 100 mm, red
LTLNC100-G	LED line light 100 mm, green
LTLNC100-B	LED line light 100 mm, blue
LTLNC100-IR850	LED line light 100 mm, IR 850 nm
LTLNC150-W	LED line light 150 mm, white
LTLNC150-R	LED line light 150 mm, red
LTLNC150-G	LED line light 150 mm, green
LTLNC150-B	LED line light 150 mm, blue
LTLNC150-IR850	LED line light 150 mm, IR 850 nm
LTLNC200-W	LED line light 200 mm, white
LTLNC200-R	LED line light 200 mm, red
LTLNC200-G	LED line light 200 mm, green
LTLNC200-B	LED line light 200 mm, blue
LTLNC200-IR850	LED line light 200 mm, IR 850 nm
LTLNC300-W	LED line light 300 mm, white
LTLNC300-R	LED line light 300 mm, red
LTLNC300-G	LED line light 300 mm, green
LTLNC300-B	LED line light 300 mm, white
LTLNC300-IR850	LED line light 300 mm, IR 850 nm



LTLNM series

Flicker free high power focused modular LED line lights

LTLNM-0200-N-FC-W	Modular LED line light, 200mm length, near field focusing, fan cooling, white
LTLNM-0200-N-D-FC-W	Modular LED line light, 200mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0200-F-FC-W	Modular LED line light, 200mm length, far field focusing, fan cooling, white
LTLNM-0200-F-D-FC-W	Modular LED line light, 200mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0200-C-FC-W	Modular LED line light, 200mm length, collimated, fan cooling, white
LTLNM-0200-C-D-FC-W	Modular LED line light, 200mm length, collimated, diffuser, fan cooling, white
LTLNM-0400-N-FC-W	Modular LED line light, 400mm length, near field focusing, fan cooling, white
LTLNM-0400-N-D-FC-W	Modular LED line light, 400mm length, near field focusing, diffuser, fan cooling, white

LTLNM-2000-F-D-FC-W	Modular LED line light, 2000mm length, far field focusing, diffuser, fan cooling, white
LTLNM-2000-C-FC-W	Modular LED line light, 2000mm length, collimated, fan cooling, white
LTLNM-2000-C-D-FC-W	Modular LED line light, 2000mm length, collimated, diffuser, fan cooling, white



LTLNE series

High power enhanced LED line lights

LTLNE-300-N-PC-W	LED line light, direct, 300mm length, near field focusing, passive cooling, white
LTLNE-300-N-FC-W	LED line light, direct, 300mm length, near field focusing, fan cooling, white
LTLNE-300-N-D-PC-W	LED line light, direct, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-N-D-FC-W	LED line light, direct, 300mm length, near field focusing, diffuser, fan cooling, white
LTLNE-300-F-PC-W	LED line light, direct, 300mm length, far field focusing, passive cooling, white
LTLNE-300-F-FC-W	LED line light, direct, 300mm length, far field focusing, fan cooling, white
LTLNE-300-F-D-PC-W	LED line light, direct, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-F-D-FC-W	LED line light, direct, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-C-PC-W	LED line light, direct, 300mm length, collimated, passive cooling, white
LTLNE-300-C-FC-W	LED line light, direct, 300mm length, collimated, fan cooling, white
LTLNE-300-C-D-PC-W	LED line light, direct, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-C-D-FC-W	LED line light, direct, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-CX-N-PC-W	LED line light, coaxial, 300mm length, near field focusing, passive cooling, white
LTLNE-300-CX-N-FC-W	LED line light, coaxial, 300mm length, near field focusing, fan cooling, white
LTLNE-300-CX-N-D-PC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-CX-N-D-FC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, fan cooling, white
LTLNE-300-CX-F-PC-W	LED line light, coaxial, 300mm length, far field focusing, passive cooling, white
LTLNE-300-CX-F-FC-W	LED line light, coaxial, 300mm length, far field focusing, fan cooling, white
LTLNE-300-CX-F-D-PC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-CX-F-D-FC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-CX-C-PC-W	LED line light, coaxial, 300mm length, collimated, passive cooling, white
LTLNE-300-CX-C-FC-W	LED line light, coaxial, 300mm length, collimated, fan cooling, white
LTLNE-300-CX-C-D-PC-W	LED line light, coaxial, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-CX-C-D-FC-W	LED line light, coaxial, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-MR-N-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, passive cooling, white
LTLNE-300-MR-N-FC-W	LED line light, 45° mirror, 300mm length, near field focusing, fan cooling, white
LTLNE-300-MR-N-D-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, passive cooling, white
LTLNE-300-MR-F-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, fan cooling, white
LTLNE-300-MR-F-D-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-D-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-MR-C-PC-W	LED line light, 45° mirror, 300mm length, collimated, passive cooling, white
LTLNE-300-MR-C-FC-W	LED line light, 45° mirror, 300mm length, collimated, fan cooling, white
LTLNE-300-MR-C-D-PC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-MR-C-D-FC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, fan cooling, white



CMHO series

Clamping mechanics

CMHO120 Clamping mechanics for TCxx110, TCxx120 lenses and LTCLHP120-X illuminators



COE HR LS series

57.3 mm line scan CMOS sensors for high-speed scanning

COE8KLSMCL-G Camera CMOS, Camera Link, 8192 x 1, monochrome, 77kfp, G mount

COE16KLSMCL-G Camera CMOS, Camera Link, 16384 x 1, monochrome, 55kfp, G mount
