

# TC16M120-K

Telecentric lens for 45.72 mm detectors, magnification 0.29 x, M58x0.75 FD 12.96-mount

## SPECIFICATIONS

Magnification	(x)	0.29
Image circle Ø	(mm)	43.3

### Object field of view

with APS-H KAI-16050 32.4 mm diagonal w x h 26.93 x 17.95	(mm x mm)	93.18 x 62.12
with CHR70 38 mm diagonal w x h 31.0 x 21.99	(mm x mm)	107.27 x 76.09
with 8k x 5 µm detector	(mm)	141.18
Full frame 35 mm, 43.3 mm diagonal w x h 36.0 x 24.00	(mm x mm)	124.57 x 83.04
with CMV50000 45.72 mm diagonal w x h 36.43 x 27.62	(mm x mm)	126.06 x 95.56

### Optical specifications

Working distance (1)	(mm)	331.6
wF/# (2)		16
Telecentricity typical (max) (3)	(deg)	< 0.05 (0.08)
Distortion typical (max) (4)	(%)	< 0.05 (0.10)
Field depth (5)	(mm)	15.8
CTF@ 50 lp/mm	(%)	> 40

### Mechanical specifications

Mount (6)		M58x0.75 FD12.96
Phase adjustment (7)		
Length (8)	(mm)	571.8
Diameter	(mm)	180
Mass	(g)	5318

Last update: 2020-07-16

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators

**LTCLHP120-G** Telecentric HP illuminator, beam diameter 150 mm, green



COE HR AS series

29 MP, 48MP and 71MP area scan cameras for high-speed applications

**COE29MUSB3IR-K** Area scan camera CCD, USB3, 6576 x 4384 monochrome, 35mm, 2fps, IR Cut filter, K mount

**COE29CUSB3IR-K** Area scan camera CCD, USB3, 6576 x 4384 color, 35mm, 2fps, IR cut, IR Cut filter, K mount

**COE29MUSB3IR-F** Area scan camera CCD, USB3, 6576 x 4384 monochrome, 35mm, 2fps, IR Cut filter, F-mount

**COE29CUSB3IR-F** Area scan camera CCD, USB3, 6576 x 4384 color, 35mm, 2fps, IR cut, IR Cut filter, F-mount

**COE29MCLIR-K** Area scan camera CCD, Camera Link, 6576 x 4384 monochrome, 35mm, 4fps, IR Cut filter, K mount

**COE29CCLIR-K** Area scan camera CCD, Camera Link, 6576 x 4384 color, 35mm, 4fps, IR Cut filter, K mount



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

COE29MCLIR-F	Area scan camera CCD, Camera Link, 6576 x 4384 monochrome, 35mm, 4fps, IR Cut filter, F-mount
COE29CCLIR-F	Area scan camera CCD, Camera Link, 6576 x 4384 color, 35mm, 4fps, IR Cut filter, F-mount
COE29MUSB3SK-K	Area scan camera CCD, USB3, 6576 x 4384 monochrome, 35mm, 2fps, skylight/glass filter, K mount
COE29CUSB3SK-K	Area scan camera CCD, USB3, 6576 x 4384 color, 35mm, 2fps, skylight/glass filter, K mount
COE29MUSB3SK-F	Area scan camera CCD, USB3, 6576 x 4384 monochrome, 35mm, 2fps, skylight/glass filter, F-mount
COE29CUSB3SK-F	Area scan camera CCD, USB3, 6576 x 4384 color, 35mm, 2fps, skylight/glass filter, F-mount
COE29MCLSK-K	Area scan camera CCD, Camera Link, 6576 x 4384 monochrome, 35mm, 4fps, skylight/glass filter, K mount
COE29CCLSK-K	Area scan camera CCD, Camera Link, 6576 x 4384 color, 35mm, 4fps, skylight/glass filter, K mount
COE29MCLSK-F	Area scan camera CCD, Camera Link, 6576 x 4384 monochrome, 35mm, 4fps, skylight/glass filter, F-mount
COE29CCLSK-F	Area scan camera CCD, Camera Link, 6576 x 4384 color, 35mm, 4fps, skylight/glass filter, F-mount
COE50MUSB3IR-K	Area scan camera CMOS, USB3, 7920 x 6004, monochrome, 6.8fps, IR Cut filter, K mount
COE50CUSB3IR-K	Area scan camera CMOS, USB3, 7920 x 6004, color, 6.8fps, IR Cut filter, K mount
COE50MUSB3IR-F	Area scan camera CMOS, USB3, 7920 x 6004, monochrome, 6.8fps, IR Cut filter, F-mount
COE50CUSB3IR-F	Area scan camera CMOS, USB3, 7920 x 6004, color, 6.8fps, IR Cut filter, F-mount
COE50MCLIR-K	Area scan camera CMOS, Camera Link, 7920 x 6004, monochrome, 27.3fps, IR Cut filter, K mount
COE50CCLIR-K	Area scan camera CMOS, Camera Link, 7920 x 6004, color, 27.3fps, IR Cut filter, K mount
COE50MCLIR-F	Area scan camera CMOS, Camera Link, 7920 x 6004, monochrome, 27.3fps, IR Cut filter, F-mount
COE50CCLIR-F	Area scan camera CMOS, Camera Link, 7920 x 6004, color, 27.3fps, IR Cut filter, F-mount
COE50MUSB3SK-K	Area scan camera CMOS, USB3, 7920 x 6004, monochrome, 6.8fps, skylight/glass filter, K mount
COE50CUSB3SK-K	Area scan camera CMOS, USB3, 7920 x 6004, color, 6.8fps, skylight/glass filter, K mount
COE50MUSB3SK-F	Area scan camera CMOS, USB3, 7920 x 6004, monochrome, 6.8fps, skylight/glass filter, F-mount
COE50CUSB3SK-F	Area scan camera CMOS, USB3, 7920 x 6004, color, 6.8fps, skylight/glass filter, F-mount
COE50MCLSK-K	Area scan camera CMOS, Camera Link, 7920 x 6004, monochrome, 27.3fps, skylight/glass filter, K mount
COE50CCLSK-K	Area scan camera CMOS, Camera Link, 7920 x 6004, color, 27.3fps, skylight/glass filter, K mount
COE50MCLSK-F	Area scan camera CMOS, Camera Link, 7920 x 6004, monochrome, 27.3fps, skylight/glass filter, F-mount
COE50CCLSK-F	Area scan camera CMOS, Camera Link, 7920 x 6004, color, 27.3fps, skylight/glass filter, F-mount
COE71MUSB3IR-K	Area scan camera CMOS, USB3, 10000 x 7094, monochrome, 3fps, IR Cut filter, K mount
COE71CUSB3IR-K	Area scan camera CMOS, USB3, 10000 x 7094, color, 3fps, IR Cut filter, K mount
COE71MUSB3IR-F	Area scan camera CMOS, USB3, 10000 x 7094, monochrome, 3fps, IR Cut filter, F-mount
COE71CUSB3IR-F	Area scan camera CMOS, USB3, 10000 x 7094, color, 3fps, IR Cut filter, F-mount
COE71MCLIR-K	Area scan camera CMOS, Camera Link, 10000 x 7094, monochrome, 3fps, IR Cut filter, K mount
COE71CCLIR-K	Area scan camera CMOS, Camera Link, 10000 x 7094, color, 3fps, IR Cut filter, K mount
COE71MCLIR-F	Area scan camera CMOS, Camera Link, 10000 x 7094, monochrome, 3fps, IR Cut filter, F-mount
COE71CCLIR-F	Area scan camera CMOS, Camera Link, 10000 x 7094, color, 3fps, IR Cut filter, F-mount
COE71MUSB3SK-K	Area scan camera CMOS, USB3, 10000 x 7094, monochrome, 3fps, skylight/glass filter, K mount
COE71CUSB3SK-K	Area scan camera CMOS, USB3, 10000 x 7094, color, 3fps, skylight/glass filter, K mount
COE71MUSB3SK-F	Area scan camera CMOS, USB3, 10000 x 7094, monochrome, 3fps, skylight/glass filter, F-mount

COE71CUSB3SK-F	Area scan camera CMOS, USB3, 10000 x 7094, color, 3fps, skylight/glass filter, F-mount
COE71MCLSK-K	Area scan camera CMOS, Camera Link, 10000 x 7094, monochrome, 3fps, skylight/glass filter, K mount
COE71CCLSK-K	Area scan camera CMOS, Camera Link, 10000 x 7094, color, 3fps, skylight/glass filter, K mount
COE71MCLSK-F	Area scan camera CMOS, Camera Link, 10000 x 7094, monochrome, 3fps, skylight/glass filter, F-mount
COE71CCLSK-F	Area scan camera CMOS, Camera Link, 10000 x 7094, color, 3fps, skylight/glass filter, F-mount



#### COE HR AS-X series

20MP, 26MP and 29MP area scan cameras for high-speed applications

COE-260-M-10GIGE-100-IR-F	HR Area Scan camera PYTHON 25K, CMOS, 5120 x 5120, 26 MP, 4.5 pix, APS-H, Gray, 10GigE, 40 fps, F - mount, Glass filter
COE-260-M-10GIGE-100-IR-I	HR Area Scan camera PYTHON 25K, CMOS, 5120 x 5120, 26 MP, 4.5 pix, APS-H, Gray, 10GigE, 40 fps, M58x0.75 - mount, Glass filter
COE-290-M-GIGE-110-IR-F-A	HR Area Scan camera KAI29050-B1, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Gray, GigE, 4 fps, F - mount, Glass filter
COE-290-M-GIGE-110-IR-F-B	HR Area Scan camera KAI29050-B2, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Gray, GigE, 4 fps, F - mount, Glass filter
COE-290-M-GIGE-110-IR-I-A	HR Area Scan camera KAI29050-B1, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Gray, GigE, 4 fps, M58x0.75 - mount, Glass filter
COE-290-M-GIGE-110-IR-I-B	HR Area Scan camera KAI29050-B2, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Gray, GigE, 4 fps, M58x0.75 - mount, Glass filter
COE-290-C-GIGE-110-IR-F-B	HR Area Scan camera KAI29050-B2, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Color, GigE, 4 fps, F - mount, Infrared cut filter
COE-290-C-GIGE-110-IR-I-B	HR Area Scan camera KAI29050-B2, CCD, Global shutter, 6576 x 4384, 29 MP, 5.5 pix, 35 mm, Color, GigE, 4 fps, M58x0.75 - mount, Infrared cut filter