

TC2MHR024-E

High resolution telecentric lens for 1" detectors, magnification 0.508x, mount M42X1 FD=16

SPECIFICATIONS

Magnification	(x)	0.508
Image circle Ø	(mm)	16.9

Object field of view ⁸	(mm x mm or Ø)
with IMX174/IMX249 13.3 mm diag w x h 11.35 x 7.13	22.33 x 14.03
with IMX255/IMX267 16.1 mm diag w x h 14.19 x 7.51	27.93 x 14.78
with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37	Ø = 20.42
with KAI-4022/4021 21.5 mm diagonal w x h 15.2 x 15.2	Ø = 29.83
with KAI-08050 22.6 mm diagonal w x h 18.1 x 13.6 ⁽⁷⁾	Ø = 26.76

Optical specifications

Working distance ⁽¹⁾	(mm)	67.2
wF/# ⁽²⁾		16
Telecentricity typical (max) ⁽³⁾	(deg)	<0.08 (0.10)
Distortion typical (max) ⁽⁴⁾	(%)	<0.04 (0.10)
Field depth ⁽⁵⁾	(mm)	4.7
CTF@ 50 lp/mm	(%)	> 40

Mechanical specifications

Mount		M42x1 FD16.00
Phase adjustment ⁽⁹⁾		Yes
Length ⁽⁶⁾	(mm)	171.9
Diameter	(mm)	52
Mass	(g)	534

Last update: 2019-06-17

NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5 µm.
- Measured from the front end of the mechanics to the camera flange.
- With KAI-08050 (22.6 mm diagonal) detectors, the FOV of TC4MHRyyy-x lenses may show some vignetting at the image corners.
- For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators

LTCLHP024-R	Telecentric HP illuminator, beam diameter 30 mm, red
LTCLHP024-G	Telecentric HP illuminator, beam diameter 30 mm, green



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

LTCLHP024-B	Telecentric HP illuminator, beam diameter 30 mm, blue
LTCLHP024-W	Telecentric HP illuminator, beam diameter 30 mm, white



LTLA series

High-power strobed LED low angle diffused ringlights

LTLAB2-R	Diffusive strobed low angle ring light illuminator - medium size high power red
LTLAB2-G	Diffusive strobed low angle ring light illuminator - medium size high power green
LTLAB2-W	Diffusive strobed low angle ring light illuminator - medium size high power white



LTLAIC series (discontinued models)

Continuous LED low angle diffused ringlights

LT2RZF070-60-2-W-24V	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, white, 24V
LT2RZF070-60-2-R-24V	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, red, 24V
LT2RZF070-60-2-G-24V	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, green, 24V
LT2RZF070-60-2-B-24V	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, blue, 24V



LTLAIC series

Continuous LED low angle diffused ringlights

LT3RZF080-60-1-W-24V	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, white, 24V
LT3RZF080-60-1-R-24V	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, red, 24V
LT3RZF080-60-1-G-24V	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, green, 24V
LT3RZF080-60-1-B-24V	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, blue, 24V



LTLADC series

Continuous LED low angle direct ringlights

LTZZO130-75-3-W-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, white, 24V
LTZZO130-75-3-R-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, red, 24V
LTZZO130-75-3-G-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, green, 24V
LTZZO130-75-3-B-24V	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, blue, 24V



LTRNST series

LED ring illuminators - straight type

LTRN024RD	Ring LED illuminator, inner diameter 44 mm, straight type, red 630 nm
LTRN024GR	Ring LED illuminator, inner diameter 44 mm, straight type, green 525 nm
LTRN024BL	Ring LED illuminator, inner diameter 44 mm, straight type, blue 470 nm
LTRN024NW	Ring LED illuminator, inner diameter 44 mm, straight type, white



LTBC series

Continuous LED backlight

LTBC054054-W	Continuous LED backlight, 54x54 illumination area, white
LTBC054054-G	Continuous LED backlight, 54x54 illumination area, green



LTBFC series

Continuous flat side-emitting LED backlights

LTPVR070-00-1-W-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, white, 24V
LTPVR070-00-1-R-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, red, 24V
LTPVR070-00-1-G-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, green, 24V
LTPVR070-00-1-B-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, blue, 24V
LTPVRG070-00-1-W-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, white, 24V
LTPVRG070-00-1-R-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, red, 24V
LTPVRG070-00-1-G-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, green, 24V

LTPVRG070-00-1-B-24V Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, blue, 24V



LTBRDC series

Continuous LED bar lights

LTZPFL040-00-6-W-24V LED bar light, 6 LED rows, 40X26.3 illumination area, white, 24V

LTZPFL040-00-6-R-24V LED bar light, 6 LED rows, 40X26.3 illumination area, red, 24V

LTZPFL040-00-6-G-24V LED bar light, 6 LED rows, 40X26.3 illumination area, green, 24V

LTZPFL040-00-6-B-24V LED bar light, 6 LED rows, 40X26.3 illumination area, blue, 24V



CMHO series

Clamping mechanics

CMHO024 Clamping mechanics for TCxx024 lenses and LTCLHP024-X illuminators



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2024a USB3 Vision camera with Sony Pregius CMOS sensor IMX249

RT-mvBF3-2024 USB3 Vision camera with Sony Pregius CMOS sensor IMX174

RT-mvBF3-2089a USB3 Vision camera with Sony Pregius CMOS sensor IMX267

RT-mvBF3-2089 USB3 Vision camera with Sony Pregius CMOS sensor IMX255



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X104f Camera with interface GigE (1GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1216, sensor name IMX249, sensor type CMOS

RT-mvBC-XD104d Camera with interface Dual GigE (2GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1214, sensor name IMX174, sensor type CMOS

RT-mvBC-X109b Camera with interface GigE (1GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS

RT-mvBC-XD109b Camera with interface Dual GigE (2GB/s), sensor size 1", mpixel 8.95, resolution 4112 X 2176, sensor name IMX267, sensor type CMOS



COE HR AS-X series

20MP, 26MP and 29MP area scan cameras for high-speed applications

COE-200-M-POE-070-IR-C HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Gray, GigE, 6 fps, POE, C - mount, Glass filter

COE-200-C-POE-070-IR-C HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Color, GigE, 6 fps, POE, C - mount, Infrared cut filter

COE-200-M-USB-070-IR-C HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Gray, 14 fps, C - mount, Glass filter

COE-200-C-USB-070-IR-C HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Color, 14 fps, C - mount, Infrared cut filter