

TC2MHR120-E

High resolution telecentric lens for 1" detectors, magnification 0.104x, mount M42X1 FD=16

SPECIFICATIONS

Magnification	(x)	0.104
Image circle Ø	(mm)	16.5

Object field of view ⁸	(mm x mm or Ø)
with IMX174/IMX249 13.3 mm diag w x h 11.35 x 7.13	109.09 x 68.52
with IMX255/IMX267 16.1 mm diag w x h 14.19 x 7.51	136.44 x 72.21
with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37	Ø = 99.72
with KAI-4022/4021 21.5 mm diagonal w x h 15.2 x 15.2	Ø = 145.72
with KAI-08050 22.6 mm diagonal w x h 18.1 x 13.6 ⁽⁷⁾	Ø = 130.73

Optical specifications

Working distance ⁽¹⁾	(mm)	334.6
wF/# ⁽²⁾		16
Telecentricity typical (max) ⁽³⁾	(deg)	<0.07(0.10)
Distortion typical (max) ⁽⁴⁾	(%)	<0.07 (0.10)
Field depth ⁽⁵⁾	(mm)	110.9
CTF@ 50 lp/mm	(%)	> 40

Mechanical specifications

Mount		M42x1 FD16.00
Phase adjustment ⁽⁹⁾		Yes
Length ⁽⁶⁾	(mm)	452.9
Diameter	(mm)	180
Mass	(g)	4846

Last update: 2019-06-17

NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5 µm.
- Measured from the front end of the mechanics to the camera flange.
- With KAI-08050 (22.6 mm diagonal) detectors, the FOV of TC4MHRyyy-x lenses may show some vignetting at the image corners.
- For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.

COMPATIBLE PRODUCTS


Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators

LTCLHP120-R	Telecentric HP illuminator, beam diameter 150 mm, red
LTCLHP120-G	Telecentric HP illuminator, beam diameter 150 mm, green



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

LTCLHP120-W Telecentric HP illuminator, beam diameter 150 mm, white



LTCLHP CORE series

Ultra compact telecentric illuminators

LTCLCR120-R Telecentric CORE illuminator, beam dimensions $\varnothing = 156$, $x = 130$, red, 630 nm

LTCLCR120-G Telecentric CORE illuminator, beam dimensions $\varnothing = 156$, $x = 130$, green, 520 nm

LTCLCR120-W Telecentric CORE illuminator, beam dimensions $\varnothing = 156$, $x = 130$, white



LTRNST series

LED ring illuminators - straight type

LTRN120RD Ring LED illuminator, inner diameter 180 mm, straight type, red 630 nm

LTRN120GR Ring LED illuminator, inner diameter 180 mm, straight type, green 525 nm

LTRN120BL Ring LED illuminator, inner diameter 180 mm, straight type, blue 470 nm

LTRN120NW Ring LED illuminator, inner diameter 180 mm, straight type, white



LTBC series

Continuous LED backlight

LTBC174174-W Continuous LED backlight, 174x174 illumination area, white

LTBC174174-G Continuous LED backlight, 174x174 illumination area, green



LTBRDC series

Continuous LED bar lights

LTZPFL200-00-6-W-24V LED bar light, 6 LED rows, 200X26.3 illumination area, white, 24V

LTZPFL200-00-6-R-24V LED bar light, 6 LED rows, 200X26.3 illumination area, red, 24V

LTZPFL200-00-6-G-24V LED bar light, 6 LED rows, 200X26.3 illumination area, green, 24V

LTZPFL200-00-6-B-24V LED bar light, 6 LED rows, 200X26.3 illumination area, blue, 24V



CMHO series

Clamping mechanics

CMHO120 Clamping mechanics for TCxx110, TCxx120 lenses and LTCLHP120-X illuminators



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2024a USB3 Vision camera with Sony Pregius CMOS sensor IMX249

RT-mvBF3-2024 USB3 Vision camera with Sony Pregius CMOS sensor IMX174

RT-mvBF3-2089a USB3 Vision camera with Sony Pregius CMOS sensor IMX267

RT-mvBF3-2089 USB3 Vision camera with Sony Pregius CMOS sensor IMX255



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X104f Camera with interface GigE (1GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1216, sensor name IMX249, sensor type CMOS

RT-mvBC-XD104d Camera with interface Dual GigE (2GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1214, sensor name IMX174, sensor type CMOS

RT-mvBC-X109b Camera with interface GigE (1GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS

RT-mvBC-XD109b Camera with interface Dual GigE (2GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS



COE HR AS-X series

20MP, 26MP and 29MP area scan cameras for high-speed applications

COE-200-M-POE-070-IR-C HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Gray, GigE, 6 fps, POE, C - mount, Glass filter

COE-200-C-POE-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Color, GigE, 6 fps, POE, C - mount, Infrared cut filter
COE-200-M-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Gray, 14 fps, C - mount, Glass filter
COE-200-C-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Color, 14 fps, C - mount, Infrared cut filter