

TC3MHR096-C

High resolution telecentric lens for 1.1" detectors, magnification 0.153x, C-mount

SPECIFICATIONS

Magnification	(x)	0.153
Image circle Ø	(mm)	17.6
Object field of view ⁸	(mm x mm or Ø)	
with IMX174/IMX249 13.3 mm diag w x h 11.35 x 7.13		74.15 x 46.58
with IMX255/IMX267 16.1 mm diag w x h 14.19 x 7.51		92.75 x 49.08
with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37		92.54 x 67.78
with KAI-4022/4021 21.5 mm diagonal w x h 15.2 x 15.2		Ø = 99.05
with KAI-08050 22.6 mm diagonal w x h 18.1 x 13.6 ⁽⁷⁾		Ø = 88.86

Optical specifications

Working distance ⁽¹⁾	(mm)	278.6
wF/# ⁽²⁾		8
Telecentricity typical (max) ⁽³⁾	(deg)	<0.08 (0.10)
Distortion typical (max) ⁽⁴⁾	(%)	<0.08 (0.10)
Field depth ⁽⁵⁾	(mm)	25.6
CTF@ 50 lp/mm	(%)	> 55

Mechanical specifications

Mount		C
Phase adjustment ⁽⁹⁾		Yes
Length ⁽⁶⁾	(mm)	354.7
Diameter	(mm)	143
Mass	(g)	2267

Last update: 2018-06-12

NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures (higher wF/#) can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5,5 µm.
- Measured from the front end of the mechanics to the camera flange.
- With KAI-08050 (22.6 mm diagonal) detectors, the FOV of TC4MHRyyy-x lenses may show some vignetting at the image corners.
- For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.
- Indicates the availability of an integrated camera phase adjustment feature

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

LTCLHP096-R	Telecentric HP illuminator, beam diameter 120 mm, red
LTCLHP096-B	Telecentric HP illuminator, beam diameter 120 mm, blue
LTCLHP096-W	Telecentric HP illuminator, beam diameter 120 mm, white



LTCLHP CORE series
Ultra compact telecentric illuminators

LTCLCR096-R	Telecentric CORE illuminator, beam dimensions $\varnothing = 120$; x = 99, red
LTCLCR096-G	Telecentric CORE illuminator, beam dimensions $\varnothing = 120$; x = 99, green
LTCLCR096-W	Telecentric CORE illuminator, beam dimensions $\varnothing = 120$; x = 99, white



LTRNST series
LED ring illuminators - straight type

LTRN096RD	Ring LED illuminator, inner diameter 143 mm, straight type, red 630 nm
LTRN096GR	Ring LED illuminator, inner diameter 143 mm, straight type, green 525 nm
LTRN096BL	Ring LED illuminator, inner diameter 143 mm, straight type, blue 470 nm
LTRN096NW	Ring LED illuminator, inner diameter 143 mm, straight type, white



LTBC series
Continuous LED backlight

LTBC174174-W	Continuous LED backlight, 174x174 illumination area, white
LTBC174174-G	Continuous LED backlight, 174x174 illumination area, green



CMMR series
45° first surface mirrors

CMMR096	45° first surface mirror for 143 mm clamping diameter optics
---------	--



WI series
Protective windows

WI096	Protective window for 143 mm clamping diameter optics
-------	---



CMHO series
Clamping mechanics

CMHO096	Clamping mechanics for TCxx085, TCxx096 lenses and LTCLHP096-X illuminators
---------	---



CMT series
Precision alignment mechanics

CMTH096	Precision alignment mechanics for telecentric optics 096
---------	--



COE-G series
GenICam® PoE cameras

COE-053-M-POE-070-IR-C	Area Scan camera PYTHON 5000, CMOS, Global shutter, 2592 x 2048, 5.3 MP, 4.8 pix, 1", Gray, 22 fps, GigE, POE, C - mount, Glass filter
COE-053-C-POE-070-IR-C	Area Scan camera PYTHON 5000, CMOS, Global shutter, 2592 x 2048, 5.3 MP, 4.8 pix, 1", Color, 22 fps, GigE, POE, C - mount, Infrared cut filter
COE-089-M-POE-070-IR-C	Area Scan camera IMX267, CMOS, Global shutter, 4096 x 2160, 8.8 MP, 3.45 pix, 1", Gray, 13 fps, GigE, POE, C - mount, Glass filter
COE-089-C-POE-070-IR-C	Area Scan camera IMX267, CMOS, Global shutter, 4096 x 2160, 8.8 MP, 3.45 pix, 1", Color, 13 fps, GigE, POE, C - mount, Infrared cut filter
COE-123-M-POE-080-IR-C	Area Scan camera IMX304, CMOS, Global shutter, 4096 x 3000, 12.3 MP, 3.45 pix, 1.1", Gray, 9.4 fps, GigE, POE, C - mount, Glass filter
COE-123-C-POE-080-IR-C	Area Scan camera IMX304, CMOS, Global shutter, 4096 x 3000, 12.3 MP, 3.45 pix, 1.1", Color, 9.4 fps, GigE, POE, C - mount, Infrared cut filter



COE-U series

USB 3.0 GenICam® cameras

COE-053-M-USB-070-IR-C	Area Scan camera PYTHON 5000, CMOS, Global shutter, 2592 x 1944, 5 MP, 4.8 pix, 1", Gray, 60 fps, USB 3.0, C - mount, Glass filter
COE-053-C-USB-070-IR-C	Area Scan camera PYTHON 5000, CMOS, Global shutter, 2592 x 1944, 5 MP, 4.8 pix, 1", Color, 30 fps, USB 3.0, C - mount, Infrared cut filter
COE-089-M-USB-070-IR-C	Area Scan camera IMX267, CMOS, Global shutter, 4096 x 2160, 8.8 MP, 3.45 pix, 1", Gray, 32 fps, USB 3.0, C - mount, Glass filter
COE-089-C-USB-070-IR-C	Area Scan camera IMX267, CMOS, Global shutter, 4096 x 2160, 8.8 MP, 3.45 pix, 1", Color, 32 fps, USB 3.0, C - mount, Infrared cut filter
COE-123-M-USB-080-IR-C	Area Scan camera IMX304, CMOS, Global shutter, 4096 x 3000, 12.3 MP, 3.45 pix, 1.1", Gray, 23 fps, USB 3.0, C - mount, Glass filter
COE-123-C-USB-080-IR-C	Area Scan camera IMX304, CMOS, Global shutter, 4096 x 3000, 12.3 MP, 3.45 pix, 1.1", Color, 23 fps, USB 3.0, C - mount, Infrared cut filter



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2089a	USB3 Vision camera with Sony Pregius CMOS sensor IMX267
RT-mvBF3-2089	USB3 Vision camera with Sony Pregius CMOS sensor IMX255
RT-mvBF3-2124a	USB3 Vision camera with Sony Pregius CMOS sensor IMX304
RT-mvBF3-2124	USB3 Vision camera with Sony Pregius CMOS sensor IMX253



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X109b	Camera with interface GigE (1GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS
RT-mvBC-XD109b	Camera with interface Dual GigE (2GB/s), sensor size 1", mpixel 8.95, resolution 4112 X 2176, sensor name IMX267, sensor type CMOS
RT-mvBC-X1012b	Camera with interface GigE (1GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS
RT-mvBC-XD107	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 7.1, resolution 3216 x 2208, sensor name IMX420, sensor type CMOS
RT-mvBC-XD1012b	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS



COE HR AS-X series

20MP, 26MP and 29MP area scan cameras for high-speed applications

COE-200-M-POE-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Gray, GigE, 6 fps, POE, C - mount, Glass filter
COE-200-C-POE-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Color, GigE, 6 fps, POE, C - mount, Infrared cut filter
COE-200-M-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Gray, 14 fps, C - mount, Glass filter
COE-200-C-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 x 3648, 20.4 MP, 2.4 pix, 1", Color, 14 fps, C - mount, Infrared cut filter