

# TC4MHR024-C

High resolution telecentric lens for 4/3" detectors, magnification 0.700x, C-mount

## SPECIFICATIONS

Magnification	(x)	0.700
Image circle Ø	(mm)	21.6

Object field of view <sup>8</sup>	(mm x mm or Ø)
with IMX174/IMX249 13.3 mm diag w x h 11.35 x 7.13	16.21 x 10.18
with IMX255/IMX267 16.1 mm diag w x h 14.19 x 7.51	20.27 x 10.73
with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37	20.23 x 14.82
with KAI-4022/4021 21.5 mm diagonal w x h 15.2 x 15.2	21.7 x 21.7
with KAI-08050 22.6 mm diagonal w x h 18.1 x 13.6 <sup>(7)</sup>	25.9 x 19.4

## Optical specifications

Working distance <sup>(1)</sup>	(mm)	67.2
wF/# <sup>(2)</sup>		16
Telecentricity typical (max) <sup>(3)</sup>	(deg)	<0.08 (0.10)
Distortion typical (max) <sup>(4)</sup>	(%)	<0.04 (0.10)
Field depth <sup>(5)</sup>	(mm)	2.4
CTF@ 50 lp/mm	(%)	> 30

## Mechanical specifications

Mount		C
Phase adjustment <sup>(9)</sup>		Yes
Length <sup>(6)</sup>	(mm)	194.8
Diameter	(mm)	45
Mass	(g)	519

Last update: 2020-01-15

## NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number (wF/#): the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5 µm.
- Measured from the front end of the mechanics to the camera flange.
- With KAI-08050 (22.6 mm diagonal) detectors, the FOV of TC4MHRyyy-x lenses may show some vignetting at the image corners.
- For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTCLHP series

High-performance telecentric illuminators

LTCLHP024-R	Telecentric HP illuminator, beam diameter 30 mm, red
LTCLHP024-G	Telecentric HP illuminator, beam diameter 30 mm, green



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

<a href="#">LTCLHP024-B</a>	Telecentric HP illuminator, beam diameter 30 mm, blue
<a href="#">LTCLHP024-W</a>	Telecentric HP illuminator, beam diameter 30 mm, white



LTLA series

High-power strobed LED low angle diffused ringlights

<a href="#">LTLAB2-R</a>	Diffusive strobed low angle ring light illuminator - medium size high power red
<a href="#">LTLAB2-G</a>	Diffusive strobed low angle ring light illuminator - medium size high power green
<a href="#">LTLAB2-W</a>	Diffusive strobed low angle ring light illuminator - medium size high power white
<a href="#">LTLAC1-W</a>	Diffusive strobed low angle ring light illuminator - large size medium power white



LTLAIC series (discontinued models)

Continuous LED low angle diffused ringlights

<a href="#">LT2RZF070-60-2-W-24V</a>	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, white, 24V
<a href="#">LT2RZF070-60-2-R-24V</a>	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, red, 24V
<a href="#">LT2RZF070-60-2-G-24V</a>	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, green, 24V
<a href="#">LT2RZF070-60-2-B-24V</a>	LED ringlight, 2 LED rows, 76.2 mm outer diameter, 60°, blue, 24V



LTLAIC series

Continuous LED low angle diffused ringlights

<a href="#">LT3RZF080-60-1-W-24V</a>	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, white, 24V
<a href="#">LT3RZF080-60-1-R-24V</a>	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, red, 24V
<a href="#">LT3RZF080-60-1-G-24V</a>	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, green, 24V
<a href="#">LT3RZF080-60-1-B-24V</a>	LED ringlight, 1 LED row, 81 mm outer diameter, 60°, blue, 24V



LTLADC series

Continuous LED low angle direct ringlights

<a href="#">LTZZO130-75-3-W-24V</a>	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, white, 24V
<a href="#">LTZZO130-75-3-R-24V</a>	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, red, 24V
<a href="#">LTZZO130-75-3-G-24V</a>	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, green, 24V
<a href="#">LTZZO130-75-3-B-24V</a>	LED low angle ringlight, 3 LED rows, outer diameter 131 mm, 75°, blue, 24V



LTRNST series

LED ring illuminators - straight type

<a href="#">LTRN024RD</a>	Ring LED illuminator, inner diameter 44 mm, straight type, red 630 nm
<a href="#">LTRN024GR</a>	Ring LED illuminator, inner diameter 44 mm, straight type, green 525 nm
<a href="#">LTRN024BL</a>	Ring LED illuminator, inner diameter 44 mm, straight type, blue 470 nm
<a href="#">LTRN024NW</a>	Ring LED illuminator, inner diameter 44 mm, straight type, white



LTRNDC series

Continuous LED direct ringlights

<a href="#">LTZGK070-45-3-W-24V</a>	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, white, 24V
<a href="#">LTZGK070-45-3-R-24V</a>	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, red, 24V
<a href="#">LTZGK070-45-3-G-24V</a>	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, green, 24V
<a href="#">LTZGK070-45-3-B-24V</a>	LED ringlight, 3 LED rows, outer diameter 70 mm, 45°, blue, 24V



LTBC series

Continuous LED backlight

<a href="#">LTBC054054-W</a>	Continuous LED backlight, 54x54 illumination area, white
<a href="#">LTBC054054-G</a>	Continuous LED backlight, 54x54 illumination area, green



LTBFC series

Continuous flat side-emitting LED backlights

LTPVRG31X58-00-1-W-24V	Flat side-emitting LED backlight, thin borders, 31X58 mm illumination area, white, 24V
LTPVRG31X58-00-1-R-24V	Flat side-emitting LED backlight, thin borders, 31X58 mm illumination area, red, 24V
LTPVRG31X58-00-1-G-24V	Flat side-emitting LED backlight, thin borders, 31X58 mm illumination area, green, 24V
LTPVRG31X58-00-1-B-24V	Flat side-emitting LED backlight, thin borders, 31X58 mm illumination area, blue, 24V



LTBRDC series

Continuous LED bar lights

LTPPFL040-00-6-W-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, white, 24V
LTPPFL040-00-6-R-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, red, 24V
LTPPFL040-00-6-G-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, green, 24V
LTPPFL040-00-6-B-24V	LED bar light, 6 LED rows, 40X26.3 illumination area, blue, 24V



CMHO series

Clamping mechanics

CMHO024	Clamping mechanics for TCxx024 lenses and LTCLHP024-X illuminators
---------	--



Accessories

Accessories and add-ons to make the most of Opto Engineering lenses.

TCFILTER	Filter mount for telecentric lenses
----------	-------------------------------------



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2089a	USB3 Vision camera with Sony Pregius CMOS sensor IMX267
RT-mvBF3-2089	USB3 Vision camera with Sony Pregius CMOS sensor IMX255
RT-mvBF3-2124a	USB3 Vision camera with Sony Pregius CMOS sensor IMX304
RT-mvBF3-2124	USB3 Vision camera with Sony Pregius CMOS sensor IMX253



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X109b	Camera with interface GigE (1GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS
RT-mvBC-XD109b	Camera with interface Dual GigE (2GB/s), sensor size 1", mpixel 8.95, resolution 4112 X 2176, sensor name IMX267, sensor type CMOS
RT-mvBC-X1012b	Camera with interface GigE (1GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS
RT-mvBC-XD107	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 7.1, resolution 3216 x 2208, sensor name IMX420, sensor type CMOS
RT-mvBC-XD1012b	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS



COE HR AS-X series

20MP, 26MP and 29MP area scan cameras for high-speed applications

COE-200-M-POE-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Gray, GigE, 6 fps, POE, C - mount, Glass filter
COE-200-C-POE-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Color, GigE, 6 fps, POE, C - mount, Infrared cut filter
COE-200-M-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Gray, 14 fps, C - mount, Glass filter
COE-200-C-USB-070-IR-C	HR Area Scan camera IMX183, CMOS, Rolling shutter, 5472 × 3648, 20.4 MP, 2.4 pix, 1", Color, 14 fps, C - mount, Infrared cut filter