

**overview**

- 1392 × 1040 px
- Sony ICX285
- 2/3" CCD
- 20 fps
- Gigabit Ethernet
- Phase-Out starting 04/19, alternative via sales



**technical data**

**sensor information**

sensor	Sony ICX285
resolution	1392 × 1040 px
exposure time	0,004 ... 60000 ms
pixel size	6.45 × 6.45 µm
shutter type	Global shutter
sensor type	2/3" CCD

**acquisition formats**

image formats, interface frame rate max.	Full Frame, 1392 × 1040 px, max. 20 fps Full Frame HQ, 1392 × 1040 px, max. 10 fps Binning 2×2 HQ, 696 × 520 px, max. 19 fps Binning 2×2, 696 × 520 px, max. 39 fps Binning 1×2 HQ, 1392 × 520 px, max. 19 fps Binning 1×2, 1392 × 520 px, max. 39 fps Binning 2×1 HQ, 696 × 1040 px, max. 10 fps Binning 2×1, 696 × 1040 px, max. 20 fps
--	--

pixel formats	Mono8 Mono12 Mono12 Packed
---------------	----------------------------------

**image preprocessing**

analog controls	Gain (0 ... 20 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono NIR

**camera features**

synchronization	free running trigger sequencer
trigger sources	Hardware software ActionCommand
trigger delay	0 ... 2 sec, tracking and buffering of up to 512 trigger signals
sequencer	Automated control for series of images using different sets of parameters
sequencer parameter	exposure time gain factor
digital inputs	1 input line (with Debouncer)
digital outputs	1 output line
internal image buffer	32 MB

**interfaces and connectors**

data interface	Gigabit Ethernet, Transfer rate 1000 Mb/Sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 4 pins
power supply	M8 / 3 pins

**mechanical data**

lens mount	C-mount
width	36 mm
height	36 mm
depth	48 mm
weight	≤ 90 g

# TXG14NIR

Gigabit Ethernet, 1,4 Megapixel, Monochrome

Article number: 11044473

## technical data

### mechanical data

material housing: aluminum

### electrical data

voltage supply range +Vs 8 ... 30 V DC

power consumption approx. 4,0 W

### environmental conditions

operating temperature +5 ... +50 °C

humidity 10 ... 90 % (non-condensing)

### environmental conditions

protection class IP 40

### conformity

conformity CE  
RoHS  
FCC  
UL  
EAC

## dimension drawing

