

overview

- 1920 × 1200 px
- Sony IMX174
- 1/1.2" CMOS
- 166 fps
- USB 3.0



technical data

sensor information

sensor	Sony IMX174
resolution	1920 × 1200 px
exposure time	0,045 ... 60000 ms
pixel size	5.86 × 5.86 µm
shutter type	Global shutter
sensor type	1/1.2" CMOS

acquisition formats

image formats, interface frame rate max.	Full Frame, 1920 × 1200 px, max. 166 fps Binning 2×2, 960 × 600 px, max. 166 fps Binning 2×1, 960 × 1200 px, max. 166 fps Binning 1×2, 1920 × 600 px, max. 166 fps
pixel formats	Mono8 Mono10 Mono12 Mono12 Packed

image preprocessing

analog controls	Gain (0 ... 48 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono

camera features

synchronization	free running trigger
trigger sources	Hardware software

camera features

trigger delay	0 ... 2 sec, tracking and buffering of up to 256 trigger signals
internal image buffer	469 MB 71 images (Trigger Mode) 1 image (Free Running Mode)

interfaces and connectors

data interface	USB 3.0, Transfer Rate 5000 Mbits/sec, Connector: USB 3.0 Micro B
process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)
power supply	via USB 3.0 interface

mechanical data

lens mount	C-mount
width	29 mm
height	29 mm
depth	38 mm
weight	≤ 90 g
material	zinc die casting, nickel-plated, IP 40

electrical data

power consumption	approx. 2,8 W @ 165 fps
operating voltage	5 VDC (via USB3.0 interface)

non-volatile memory

flash memory size	128 kB
-------------------	--------

environmental conditions

operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

technical data

digital I/Os

lines
 1 input line
 1 output line
 2 general purpose lines

conformity

conformity
 CE
 RoHS
 EAC

dimension drawing

