

FUJINON

型番	Due dook Name	Ver.3.0
工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工工	Product Name	TF4XA-1
焦点距離 [mm]	Focal length [mm]	4
	(design value)	(4.12)
絞り範囲 (F値)	Iris range (Fnumber)	F2.2-F16·Close
画角 (H × V)	Angle of view	64.5° × 49.1° (1/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance	∞ - 100
	(from front of lens barrel) [mm]	
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M27 \times 0.5 (INSIDE)
		M30.5 \times 0.5 (OUTSIDE)
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	100
適合センサーサイズ (標準)	Sensor size (std.)	1/3" (6.7μm)
適合センサーサイズ (最大)	Sensor size (max.)	1/3" (6.7µm)
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	14.01
フランジバック [mm]	Flange back [mm]	17.526
入射瞳位置 (マウント面から) [mm]	Entrance pupil position	-30.61
	(from Mount) [mm]	
射出瞳位置 (結像面より) [mm]	Exit pupil position	-116.95
	(from image plane) [mm]	
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-26.71
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	13.41
主点間隔 [mm]	Distance between the principal points [mm]	40.12
TVディストーション [%]	TV distortion [%]	-3.59
外形寸法 [mm]	Dimension [mm]	φ30.5 × 44.0
主光線入射角度 [°]	Chief Ray Angle [°]	1.26
周辺光量比 (F4.0·対角端) [%]	Relative illumination [%]	95
	(Aperture: F4.0,	
	Image height : at diagonal)	
周辺光量比 (開放・対角端) [%]	Relative illumination [%]	55
	(Aperture: at full open,	
	Image height : at diagonal)	
使用温度範囲	Operation Temperature Range	-10℃ ~ +50℃
保存温度範囲	Storage Temperature Range	-20℃ ~ +60℃
N I /皿/又半5四	Storage reinperature Kange	-20 C 70 TOU C

These specifications are subject to change without notice.