

OUTLINE

Ø1.31 [33.3]

USED ON: MATERIAL: P/N SUFFIX DEFINITION THE CONTENTS OF THIS UNLESS OTHERWISE SPECIFIED DOCUMENT ARE PROPRIETARY -1 CONVERSION COATING DIMENSIONS ARE IN INCHES AND TO NAVITAR. ITS USE IS -2 PAINTING INCLUDE CHEMICALLY APPLIED AUTHORIZED ONLY FOR -3 MARKING OR PLATED FINISHES RESPONDING TO REQUEST FOR -R REWORK QUOTATION OR PERFORMANCE ROCHESTER. NEW YORK **TOLERANCES AS FOLLOWS** SCALE: 1:1 OF WORK FOR NAVITAR DEC. .XXX $\pm .005$ FINISH: R. PODLENA DEC. .XX DR: 0.0 inch 1.0 ±.010 .67X MINI ADAPTER FRACT. $\pm 1/64$ ANGLES CH: ±30' CONCENTRICITY .003 TIR APP: 0.0 25.0 mm SIZE **REV** 1-61001_OL **BREAK ALL SHARP EDGES** 1/18/2002 DATE DR: .005 MIN. .010 MAX. CHAMFER ALL THREADS 30° MAX. SURF. ROUGHNESS: $\sqrt{}$ Α DO NOT SCALE DRAWING SHEET 1 OF 1 TO ROOT DIAMETER

– 1.71 [43.4] ·

2.02 [51.2] (NOM.)