

		ifications - 1.1" 6.5mm F/2	2.5, 24MP	
Specifications		1.1"	1"	2/3"
Focal Length		f = 6.5mm		
Maximum diameter (Ratio)		F = 2.5 - 16		
Picture Size		10.6 x 14.1 mm	9.6 x 12.8 mm	6.6 x 8.8 mm
Angle	- Vertical - Horizontal - Diagonal	78.7 deg 95.7 deg 109.1 deg	73.0 deg 89.9 deg 103.4 deg	53.5 deg 68.1 deg 80.8 deg
Distortion		-1.51%	-1.27%	-0.68%
FOV	- Vertical	190mm	172mm	117mm
(@MOD)	 Horizontal 	256mm	231mm	157mm
	- Diagonal	323mm	292mm	197mm
Minimum Focus Distance		0.1m		
Flange Focus		17.526mm in air		
Back Focus		10.9mm in air		
Filter Screw Size		M82x0.75		
Clear Aperture Front / Rear		Ø46mm / Ø18.5mm		
Mount		C-Mount		
Exit Pupil		-61.7mm		
Temperature Range		- 10 ~ + 50 deg. C		
Storage Temperature Range		- 20 ~ + 60 deg. C		
Resolution	Center / Corner	200 lp/mm / 100 lp/mm		

OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES SCALE: 1:1	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAVITAR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAVITAR IS PROHIBITED.	ROCHESTER, NEW YORK		
WEIGHT: SEE TABLE DR BY: PB CH BY: J. WILLIAMSON	0.0 inch 1.0	LENS	S, 6.5mm, F/2.5, 1.1", 24MP C-	MNT
PROJECT #: DO NOT SCALE DRAWING		SIZE	PART NUMBER	REV
DATE DR: 11/9/2018	$\oplus \ominus$	В	NMV-6M1.1	С