

# CB244P1500 | DATASHEET

## Power cable, side 1 M8 connector straight, side 2 cable end - 2 m - type 1 labels



Opto Engineering® provides various kinds of cables to match our offer of illuminators, optics, cameras and accessories.

All the cables we offer meet industrial standards of robustness and durability.



### SPECIFICATIONS

#### Electrical specifications

Type		Power
Number of poles		4
Conductor cross section	(AWG)	24
Cable diameter	(mm)	5
Cable length	(m)	2
Cable insulation material		PVC
Bending cycles	(cycles)	-
Minimum bending radius	(mm)	-
Side 1		M8 straight plug female connector
Side 2		Flying leads
Other		Type 1 labels
Voltage rating	(VDC)	24
Current rating	(A)	2

#### Environment

Operating temperature	(°C)	-25-+80
-----------------------	------	---------

### COMPATIBLE PRODUCTS

This products is compatible with:

- LTCLHP series
- LTCLHP CORE series
- LTCL4K series
- TCCX series
- LTPR series
- LTPRHP3W series
- LTPRSMHP3W series
- LTSCHP series

### COMPATIBLE PRODUCTS


Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.

CONNECTOR PINOUT



Device side

Pin	Function	Cable color
1	Earth	Yellow/Green
2	Ground	Black
3	Anode	Blue
4	Power supply (+12/24 V)	Brown

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.