



31 max.  
adjustable  
length

M4  
locking  
screw

90°  
45°  
Optical  
axis

2 x M4  
locking  
screw

1:3

Optical  
axis

Material		N.A.		Mass		898 g		Scale		1:2	
Surface treatment		N.A.		Part No.		CO22529					
Geometrical tolerance (ISO 2768-2)				Class	K	Undimensioned bevels		0.5x45°			
Linear tolerance (ISO 2768-2)				Class	m	Undimensioned radii		R 0.5			
0.5 ±3	>3± 6	>6± 30	>30± 120	>120 ±400	>400± 1000	>1000 ±2000	>2000 ±4000				
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2				
<p>OPTO ENGINEERING</p>		Date		Name		Drawing No.		Sheet			
		Designed 30/06/2014		Vasconetto		DP 22529-B		1/1			
		Drawn 01/07/2014		Vasconetto							
Checked											
<p>all dimensions are in mm</p> <p>OPTO ENGINEERING S.r.l. - Mantova, Italy - Tel. +39 0376699111 - www.opto-e.com</p>											
<p>Secret and confidential - All rights reserved - No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.r.l. - Any violation shall be legally prosecuted.</p>											