



# RT-M1614-MP2

Megapixel lens, focal length 16 mm, f# 1.4-16C, C-mount

## SPECIFICATIONS

### Optical specifications

Focal length	(mm)	16
Magnification		0.052 - 0
Image circle Ø	(mm)	11
Max detector size		2/3"
Working distance	(mm)	300 - ∞
F/#		1.4 - 16C
Back focal length	(mm)	13.1
Horizontal angle of view 1	(°)	30.8
Max distortion 2	(%)	0.1

### Mechanical specifications

Mount		C
Length	(mm)	28.2
Diameter	(mm)	33.5
Filter thread	(mm)	M30.5x0.5
Mass	(g)	60
Focus lock screws		Yes
Iris lock screws		Yes

Last update: 2021-06-11

## NOTES

1. Horizontal angle of view while using max detector size.
2. Max distortion while using max detector size.

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



### LTDM series

High power strobed LED domes

LTDMA1-R	Diffusive strobed dome illuminator - small size medium power red
LTDMA1-G	Diffusive strobed dome illuminator - small size medium power green
LTDMA1-W	Diffusive strobed dome illuminator - small size medium power white
LTDMB2-R	Diffusive strobed dome illuminator - medium size high power red
LTDMB2-G	Diffusive strobed dome illuminator - medium size high power green
LTDMB2-W	Diffusive strobed dome illuminator - medium size high power white
LTDMC1-W	Diffusive strobed dome illuminator - large size medium power white
LTDMC2-R	Diffusive strobed dome illuminator - large size high power red
LTDMC2-G	Diffusive strobed dome illuminator - large size high power green
LTDMC2-W	Diffusive strobed dome illuminator - large size high power white



### LTDMLA series

High power strobe dome + low angle illumination systems

LTDMLAB2-WW	Diffusive strobed dome + low angle illumination system - medium size high power white
-------------	---



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

[LTDMLAC1-WW](#) Diffusive strobed dome + low angle illumination system - large size medium power white

---

[LTDMLAC2-WW](#) Diffusive strobed dome + low angle illumination system - large size high power white

---



COE-G series

GenICam® PoE C-mount cameras

---

[COE-023-M-POE-050-IR-C](#) Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", mono, 51 fps, GigE, POE, C - mount, Glass filter

[COE-023-C-POE-050-IR-C](#) Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", color, 51 fps, GigE, POE, C - mount, Infrared cut filter

[COE-050-M-POE-050-IR-C](#) Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", mono, 23.5 fps, GigE, POE, C - mount, Glass filter

[COE-050-C-POE-050-IR-C](#) Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", color, 23.5 fps, GigE, POE, C - mount, Infrared cut filter

---



mvBlueCOUGAR series



GigE / Dual GigE cameras with Smart Features

---

[RT-mvBC-X105b](#) Camera with interface GigE (1GB/s), sensor size 2/3", mpixel 5.07, resolution 2464 x 2056, sensor name IMX264, sensor type CMOS

[RT-mvBC-XD105a](#) Camera with interface Dual GigE (2GB/s), sensor size 2/3", mpixel 5.01, resolution 2448 x 2048, sensor name IMX250, sensor type CMOS

---

---

---

---



COE-U series

GenICam® C-mount USB3 cameras

---

[COE-050-M-USB-050-IR-C](#) Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", mono, 35 fps, USB 3.0, C - mount, Glass filter

---



mvBlueFOX3-2 series



USB3 cameras with Smart Features

---

[RT-mvBF3-2051a](#) USB3 Vision camera with Sony Pregius CMOS sensor IMX264

[RT-mvBF3-2051](#) USB3 Vision camera with Sony Pregius CMOS sensor IMX250

---