

# EN5MP0816

Fixed focal 5 Megapixel lens, focal length 8 mm, f# 1.6 - 22, C-mount

## SPECIFICATIONS

### Optical specifications

Focal length	(mm)	8
Magnification		0.072
Image circle Ø	(mm)	11
Max detector size		2/3"
Minimum working distance	(mm)	100
F/#		1.6 - 22
Back focal length	(mm)	12.44
Angle of view with detector of 2/3" (D x H x V) <sup>1</sup>	(°)	66.8 x 55.8 x 43.3
Angle of view with detector of 1/2" (D x H x V) <sup>2</sup>	(°)	51.4 x 42.1 x 32.1
Field of view with detector of 2/3" (D x H x V)	(mm)	159.0 x 126.0 x 93.6
Distortion with detector of 2/3" <sup>3</sup>	(%)	0.73
Distortion with detector of 1/2" <sup>4</sup>	(%)	1.00

### Mechanical specifications

Mount		C
Length	(mm)	58.7
Diameter	(mm)	49.5
Mass	(g)	170
Filter thread		M40.5×0.5
Operating temperature		-10°C - +50°C
Iris lock screws		Manual with locking screw
Focus lock screws		Manual with locking screw

Last update: 2021-06-11

## NOTES

1. Angle of view while using detector of 2/3".
2. Angle of view while using detector of 1/2".
3. Max distortion while using detector of 2/3".
4. Max distortion while using detector of 1/2".

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTPR series

LED patterns projectors

LTPRHP3W-W	LED pattern projector 3W, HP, white
LTPRHP3W-R	LED pattern projector 3W, HP, red
LTPRHP3W-G	LED pattern projector 3W, HP, green
LTPRHP3W-B	LED pattern projector 3W, HP, blue
LTPRXP-W	High Power LED pattern projector, white
LTPRXP-R	High Power LED pattern projector, red



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

LTPRXP-G	High Power LED pattern projector, green
LTPRXP-B	High Power LED pattern projector, blue
LTPRUP-W	90W strobed LED pattern projector white
LTPRUP-R	90W strobed LED pattern projector red
LTPRUP-G	90W strobed LED pattern projector green
LTPRUP-B	90W strobed LED pattern projector blue



#### COE-G series

GenICam® PoE C-mount cameras

COE-004-M-POE-021-IR-C	Area Scan camera IMX287, CMOS, Global shutter, 720 x 540, 0.4 MP, 6.9 pix, 1/2.9", mono, 313 fps, GigE, POE, C - mount, Glass filter
COE-004-C-POE-021-IR-C	Area Scan camera IMX287, CMOS, Global shutter, 720 x 540, 0.4 MP, 6.9 pix, 1/2.9", color, 313 fps, GigE, POE, C - mount, Infrared cut filter
COE-013-M-POE-030-IR-C	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", mono, 90 fps, GigE, POE, C - mount, Glass filter
COE-013-C-POE-030-IR-C	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", color, 90 fps, GigE, POE, C - mount, Infrared cut filter
COE-023-M-POE-050-IR-C	Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", mono, 51 fps, GigE, POE, C - mount, Glass filter
COE-023-C-POE-050-IR-C	Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", color, 51 fps, GigE, POE, C - mount, Infrared cut filter
COE-032-M-POE-040-IR-C	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", mono, 37.5 fps, GigE, POE, C - mount, Glass filter
COE-032-C-POE-040-IR-C	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", color, 37.5 fps, GigE, POE, C - mount, Infrared cut filter
COE-050-M-POE-023-IR-C	Area Scan camera MT9P031, CMOS, Rolling shutter, 2592 x 1944, 5 MP, 2.2 pix, 1/2.5", mono, 14 fps, GigE, POE, C - mount, Glass filter
COE-050-M-POE-050-IR-C	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", mono, 23.5 fps, GigE, POE, C - mount, Glass filter
COE-050-C-POE-050-IR-C	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", color, 23.5 fps, GigE, POE, C - mount, Infrared cut filter
COE-106-M-POE-031-IR-C-2	Area Scan camera MT9J003, CMOS, Rolling shutter, 3840 x 2748, 10.6 MP, 1.67 pix, 1/2.3", mono, 11 fps, GigE, POE, C - mount, Glass filter
COE-106-C-POE-031-IR-C	Area Scan camera MT9J003, CMOS, Global shutter, 3840 x 2748, 10.6 MP, 1.67 pix, 1/2.3", color, 7 fps, GigE, POE, C - mount, Infrared cut filter



#### mvBlueCOUGAR series

GigE / Dual GigE cameras with Smart Features

RT-mvBC-X100w	Camera with interface GigE (1GB/s), sensor size 1/3", mpixel 0.36, resolution 752 x 480, sensor name MT9V034, sensor type CMOS
RT-mvBC-X100f	Camera with interface GigE (1GB/s), sensor size 1/2.9", mpixel 0.4, resolution 728 x 544, sensor name IMX287, sensor type CMOS
RT-mvBC-X102f	Camera with interface GigE (1GB/s), sensor size 1/2.9", mpixel 1.58, resolution 1456 x 1088, sensor name IMX273, sensor type CMOS
RT-mvBC-XD102f	Camera with interface Dual GigE (2GB/s), sensor size 1/2.9", mpixel 1.58, resolution 1456 x 1088, sensor name IMX273, sensor type CMOS
RT-mvBC-X104f	Camera with interface GigE (1GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1216, sensor name IMX249, sensor type CMOS
RT-mvBC-XD104d	Camera with interface Dual GigE (2GB/s), sensor size 1/1.2", mpixel 2.35, resolution 1936 x 1214, sensor name IMX174, sensor type CMOS
RT-mvBC-X104i	Camera with interface GigE (1GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX265, sensor type CMOS
RT-mvBC-XD104h	Camera with interface Dual GigE (2GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX252, sensor type CMOS
RT-mvBC-X105	Camera with interface GigE (1GB/s), sensor size 1/2.5", mpixel 5.04, resolution 2592 x 1944, sensor name MT9P031, sensor type CMOS
RT-mvBC-X105b	Camera with interface GigE (1GB/s), sensor size 2/3", mpixel 5.07, resolution 2464 x 2056, sensor name IMX264, sensor type CMOS
RT-mvBC-XD105a	Camera with interface Dual GigE (2GB/s), sensor size 2/3", mpixel 5.01, resolution 2448 x 2048, sensor name IMX250, sensor type CMOS
RT-mvBC-XD107	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 7.1, resolution 3216 x 2208, sensor name IMX420, sensor type CMOS
RT-mvBC-X109b	Camera with interface GigE (1GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS
RT-mvBC-XD109b	Camera with interface Dual GigE (2GB/s), sensor size 1", mpixel 8.95, resolution 4112 x 2176, sensor name IMX267, sensor type CMOS

<a href="#">RT-mvBC-X1010</a>	Camera with interface GigE (1GB/s), sensor size 1/2.3", mpixel 10.66, resolution 3856 x 2764, sensor name MT9J003, sensor type CMOS
<a href="#">RT-mvBC-X1012b</a>	Camera with interface GigE (1GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS
<a href="#">RT-mvBC-XD1012b</a>	Camera with interface Dual GigE (2GB/s), sensor size 1.1", mpixel 12.37, resolution 4112 x 3008, sensor name IMX304, sensor type CMOS



#### COE-U series

GeniCam® C-mount USB3 cameras

<a href="#">COE-013-M-USB-030-IR-C</a>	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", mono, 210 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-013-C-USB-030-IR-C</a>	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", color, 90 fps, USB 3.0, C - mount, Infrared cut filter
<a href="#">COE-050-M-USB-050-IR-C</a>	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", mono, 35 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-050-C-USB-050-IR-C</a>	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", color, 35 fps, USB 3.0, C - mount, Infrared cut filter
<a href="#">COE-050-C-USB-023-IR-C</a>	Area Scan camera AR0521, CMOS, Rolling shutter, 2592 x 1944, 5 MP, 2.2 pix, 1/2.5", color, 31 fps, USB 3.0, C - mount, Infrared cut filter
<a href="#">COE-003-M-USB-010-IR-C</a>	Area Scan camera PYTHON 300, CMOS, Global shutter, 640 x 480, 0.3 MP, 4.8 pix, 1/4", Gray, 814 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-003-C-USB-010-IR-C</a>	Area Scan camera PYTHON 300, CMOS, Global shutter, 640 x 480, 0.3 MP, 4.8 pix, 1/4", Color, 814 fps, USB 3.0, C - mount, Infrared cut filter
<a href="#">COE-016-M-USB-021-IR-C</a>	Area Scan camera IMX273, CMOS, Global shutter, 1440 x 1080, 1.6 MP, 3.45 pix, 1/2.9", Gray, 165 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-016-C-USB-021-IR-C</a>	Area Scan camera IMX273, CMOS, Global shutter, 1440 x 1080, 1.6 MP, 3.45 pix, 1/2.9", Color, 165 fps, USB 3.0, C - mount, Infrared cut filter



#### mvBlueFOX3-2 series

USB3 cameras with Smart Features

<a href="#">RT-mvBF3-2004</a>	USB3 vision camera with Sony Pregius CMOS sensor IMX287
<a href="#">RT-mvBF3-2016</a>	USB3 vision camera with Sony Pregius CMOS sensor IMX273
<a href="#">RT-mvBF3-2024a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX249
<a href="#">RT-mvBF3-2024</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX174
<a href="#">RT-mvBF3-2032a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX265
<a href="#">RT-mvBF3-2032</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX252
<a href="#">RT-mvBF3-2051a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX264
<a href="#">RT-mvBF3-2051</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX250
<a href="#">RT-mvBF3-2064</a>	USB3 vision camera with Sony Pregius CMOS sensor IMX178
<a href="#">RT-mvBF3-2089a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX267
<a href="#">RT-mvBF3-2089</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX255
<a href="#">RT-mvBF3-2124a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX304
<a href="#">RT-mvBF3-2124</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX253