



M4 - 6H  $\nabla$  6,50  
3x repetition @120°

M6 - 6H  $\nabla$  8,50

Pattern locking ring

Removable pattern (not included)

C-Mount (25.4) 1/32 TPI

Clamp projector here if CMHO016 is used

Phase adjustment setscrew 3x repetition @120°

Material	N.A.						Mass	293 g	Scale	1:1						
Surface treatment	N.A.						Part No.	500059								
Geometrical tolerance (ISO 2768-2)						Class	K	Undimensioned bevels								
Linear tolerance (ISO 2768-2)						Class	m	0.5x45°		Description (EN) LTPRUP-W Pattern projector assy						
0.5	>3±	>6±	>30±	>120	>400±	>1000	>2000	Undimensioned radii			Descrizione (IT) Assieme proiettore di pattern LTPRUP-W					
±3	6	30	120	±400	±1000	±2000	±4000	R 0.5								
±0.1						±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	All dimensions are in [mm]		Drawing No.	Sheet
						Date	Name		DP-500059-A		1 of 1					
						Designed	13/07/2015	A. Montagna								
						Drawn	13/07/2015	A. Montagna								
						Approved	S. Sigala		Proprietary and confidential. All rights reserved. No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.r.l. Any violation could be legally persecuted.							
						OPTO ENGINEERING S.r.l. - Mantova, ITALY - Tel. +39 0376 699111 - www.opto-engineering.com										