

# MC4K050X-F

Macro lens for 4k line scan cameras, magnification 0.50x, F-mount

## SPECIFICATIONS

### Optical specifications

Focusing (1)		near	nominal	far
Magnification	(x)	0.545	0.5	0.455
Image circle Ø	(mm)	28.7		
Working distance (2)	(mm)	177.00	189.90	205.20
Focal length	(mm)	88.0		
f/# (wF/#) (3)		6.7 (10)		
Distortion typical (max) (4)	(%)	< 0.04 (0.08)		
Field depth (5)	(mm)	2.37	2.81	3.40
CTF @ 50 lp/mm	(%)	> 50		
Image side numerical aperture		0.050		
Object side numerical aperture		0.027		

### Object field of view (mm x mm)

with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37	26.06 x 19.08	28.40 x 20.80	31.21 x 22.86
with 2k x 10 µm detector 20.48	37.61	41.00	45.05
with IMX387 21.7 mm diag w x h 18.9 x 10.6	34.64 x 19.52	37.76 x 21.28	41.49 x 23.38
with APS-C IMX342 27.9 mm diagonal w x h 22.36 x 16.77	41.02 x 30.77	44.71 x 33.54	49.13 x 36.86
with 4k x 7 µm detector 28.67	52.66	57.40	63.08

### Mechanical specifications

Length (6)	(mm)	99.5	...	...
Diameter	(mm)	64.0	...	...
Mass	(g)	542	...	...
Phase adjustment		Yes		
Mount		F	...	...

Last update: 2021-06-22

## NOTES

1. Maximum and minimum magnification changes when focusing.
2. Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
3. Working F-number: the real F-number of a lens in operating conditions.
4. Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
5. At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 7 µm.
6. Measured from the front end of the mechanics to the camera flange.

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTBC series

Continuous LED backlight

LTBC054054-W

Continuous LED backlight, 54x54 illumination area, white



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.



## LTBFC series

Continuous flat side-emitting LED backlights

LTPVR070-00-1-W-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, white, 24V
LTPVR070-00-1-R-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, red, 24V
LTPVR070-00-1-G-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, green, 24V
LTPVR070-00-1-B-24V	Flat side-emitting LED backlight, 70X70 mm illumination area, blue, 24V
LTPVRG070-00-1-W-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, white, 24V
LTPVRG070-00-1-R-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, red, 24V
LTPVRG070-00-1-G-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, green, 24V
LTPVRG070-00-1-B-24V	Flat side-emitting LED backlight, thin borders, 70X70 mm illumination area, blue, 24V



## LTDMC series (discontinued models)

Continuous LED domes

LT4WRG200-00-1-W-24V	LED dome light, 232 mm outer diameter, white, 24V
LT4WRG200-00-1-R-24V	LED dome light, 232 mm outer diameter, red, 24V
LT4WRG200-00-1-G-24V	LED dome light, 232 mm outer diameter, green, 24V
LT4WRG200-00-1-B-24V	LED dome light, 232 mm outer diameter, blue, 24V



## LTLAIC series (discontinued models)

Continuous LED low angle diffused ring lights

LT2RZF100-60-2-W-24V	LED ring light, 2 LED rows, 100 mm outer diameter, 60°, white, 24V
LT2RZF100-60-2-R-24V	LED ring light, 2 LED rows, 100 mm outer diameter, 60°, red, 24V
LT2RZF100-60-2-G-24V	LED ring light, 2 LED rows, 100 mm outer diameter, 60°, green, 24V
LT2RZF100-60-2-B-24V	LED ring light, 2 LED rows, 100 mm outer diameter, 60°, blue, 24V



## LTLA series

High power strobed LED low angle diffused ring lights

LTLAB2-R	Diffusive strobed low angle ring light illuminator - medium size high power red
LTLAB2-G	Diffusive strobed low angle ring light illuminator - medium size high power green
LTLAB2-W	Diffusive strobed low angle ring light illuminator - medium size high power white
LTLAC1-W	Diffusive strobed low angle ring light illuminator - large size medium power white
LTLAC2-R	Diffusive strobed low angle ring light illuminator - large size high power red
LTLAC2-G	Diffusive strobed low angle ring light illuminator - large size high power green
LTLAC2-W	Diffusive strobed low angle ring light illuminator - large size high power white



## LTLAIC series

Continuous LED low angle diffused ring lights

LT3RZF100-60-1-W-24V	LED ring light, 1 LED row, 105.2 mm outer diameter, 60°, white, 24V
LT3RZF100-60-1-R-24V	LED ring light, 1 LED row, 105.2 mm outer diameter, 60°, red, 24V
LT3RZF100-60-1-G-24V	LED ring light, 1 LED row, 105.2 mm outer diameter, 60°, green, 24V
LT3RZF100-60-1-B-24V	LED ring light, 1 LED row, 105.2 mm outer diameter, 60°, blue, 24V



## LTLADC series

Continuous LED low angle direct ring lights

LTZZO130-75-3-W-24V	LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, white, 24V
LTZZO130-75-3-R-24V	LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, red, 24V
LTZZO130-75-3-G-24V	LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, green, 24V
LTZZO130-75-3-B-24V	LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, blue, 24V



### Continuous LED domes

LT5WRG200-00-1-R-24V	LED dome light, 232 mm outer diameter, red, 24V
LT5WRG200-00-1-G-24V	LED dome light, 232 mm outer diameter, green, 24V
LT5WRG200-00-1-B-24V	LED dome light, 232 mm outer diameter, blue, 24V
LT5WRG200-00-1-W-24V	LED dome light, 232 mm outer diameter, white, 24V



### LTTNC series (discontinued models)

#### Continuous LED tunnel lights

LT2WRH200-00-1-W-24V	LED tunnel light, 200x183 mm, white, 24V
LT2WRH200-00-1-R-24V	LED tunnel light, 200x183 mm, red, 24V
LT2WRH200-00-1-G-24V	LED tunnel light, 200x183 mm, green, 24V
LT2WRH200-00-1-B-24V	LED tunnel light, 200x183 mm, blue, 24V



### LTDM series

#### High power strobed LED domes

LTDMC1-W	Diffusive strobed dome illuminator - large size medium power white
LTDMC2-R	Diffusive strobed dome illuminator - large size high power red
LTDMC2-G	Diffusive strobed dome illuminator - large size high power green
LTDMC2-W	Diffusive strobed dome illuminator - large size high power white



### LTDMLA series

#### High power strobe dome + low angle illumination systems

LTDMLAC1-WW	Diffusive strobed dome + low angle illumination system - large size medium power white
LTDMLAC2-WW	Diffusive strobed dome + low angle illumination system - large size high power white



### LTBRDC series

#### Continuous LED bar lights

LTZPFL080-00-6-R-24V	LED bar light, 6 LED rows, 80X26.3 illumination area, red, 24V
LTZPFL080-00-6-G-24V	LED bar light, 6 LED rows, 80X26.3 illumination area, green, 24V
LTZPFL080-00-6-B-24V	LED bar light, 6 LED rows, 80X26.3 illumination area, blue, 24V
LTZPFL080-00-6-W-24V	LED bar light, 6 LED rows, 80X26.3 illumination area, white, 24V



### LTCXC series

#### Continuous LED coaxial lights

LT2QOG070-00-X-W-24V	LED coaxial light, 70x70 mm light emitting area, white, 24V
LT2QOG070-00-X-R-24V	LED coaxial light, 70x70 mm light emitting area, red, 24V
LT2QOG070-00-X-G-24V	LED coaxial light, 70x70 mm light emitting area, green, 24V
LT2QOG070-00-X-B-24V	LED coaxial light, 70x70 mm light emitting area, blue, 24V



### LTTNC series

#### Continuous LED tunnel lights

LT3WRH200-00-1-W-24V	LED tunnel light, 227.2X163 mm, white, 24V - Opto-Engineering®.
LT3WRH200-00-1-R-24V	LED tunnel light, 227.2X163 mm, red, 24V - Opto-Engineering®.
LT3WRH200-00-1-G-24V	LED tunnel light, 227.2X163 mm, green, 24V - Opto-Engineering®.
LT3WRH200-00-1-B-24V	LED tunnel light, 227.2X163 mm, blue, 24V - Opto-Engineering®.



### LTLNC series

#### Continuous LED line lights

LTLNC100-W	LED line light 100 mm, white
LTLNC100-R	LED line light 100 mm, red
LTLNC100-G	LED line light 100 mm, green
LTLNC100-B	LED line light 100 mm, blue

LTLNC100-IR850	LED line light 100 mm, IR 850 nm
LTLNC150-W	LED line light 150 mm, white
LTLNC150-R	LED line light 150 mm, red
LTLNC150-G	LED line light 150 mm, green
LTLNC150-B	LED line light 150 mm, blue
LTLNC150-IR850	LED line light 150 mm, IR 850 nm
LTLNC200-W	LED line light 200 mm, white
LTLNC200-R	LED line light 200 mm, red
LTLNC200-G	LED line light 200 mm, green
LTLNC200-B	LED line light 200 mm, blue
LTLNC200-IR850	LED line light 200 mm, IR 850 nm
LTLNC300-W	LED line light 300 mm, white
LTLNC300-R	LED line light 300 mm, red
LTLNC300-G	LED line light 300 mm, green
LTLNC300-B	LED line light 300 mm, white
LTLNC300-IR850	LED line light 300 mm, IR 850 nm



LTLNM series

Flicker free high power focused modular LED line lights

LTLNM-0200-N-FC-W	Modular LED line light, 200mm length, near field focusing, fan cooling, white
LTLNM-0200-N-D-FC-W	Modular LED line light, 200mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0200-F-FC-W	Modular LED line light, 200mm length, far field focusing, fan cooling, white
LTLNM-0200-F-D-FC-W	Modular LED line light, 200mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0200-C-FC-W	Modular LED line light, 200mm length, collimated, fan cooling, white
LTLNM-0200-C-D-FC-W	Modular LED line light, 200mm length, collimated, diffuser, fan cooling, white
LTLNM-0400-N-FC-W	Modular LED line light, 400mm length, near field focusing, fan cooling, white
LTLNM-0400-N-D-FC-W	Modular LED line light, 400mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0400-F-FC-W	Modular LED line light, 400mm length, far field focusing, fan cooling, white
LTLNM-0400-F-D-FC-W	Modular LED line light, 400mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0400-C-FC-W	Modular LED line light, 400mm length, collimated, fan cooling, white
LTLNM-0400-C-D-FC-W	Modular LED line light, 400mm length, collimated, diffuser, fan cooling, white
LTLNM-0600-N-FC-W	Modular LED line light, 600mm length, near field focusing, fan cooling, white
LTLNM-0600-N-D-FC-W	Modular LED line light, 600mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0600-F-FC-W	Modular LED line light, 600mm length, far field focusing, fan cooling, white
LTLNM-0600-F-D-FC-W	Modular LED line light, 600mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0600-C-FC-W	Modular LED line light, 600mm length, collimated, fan cooling, white
LTLNM-0600-C-D-FC-W	Modular LED line light, 600mm length, collimated, diffuser, fan cooling, white
LTLNM-0800-N-FC-W	Modular LED line light, 800mm length, near field focusing, fan cooling, white
LTLNM-0800-N-D-FC-W	Modular LED line light, 800mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0800-F-FC-W	Modular LED line light, 800mm length, far field focusing, fan cooling, white
LTLNM-0800-F-D-FC-W	Modular LED line light, 800mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0800-C-FC-W	Modular LED line light, 800mm length, collimated, fan cooling, white
LTLNM-0800-C-D-FC-W	Modular LED line light, 800mm length, collimated, diffuser, fan cooling, white
LTLNM-1000-N-FC-W	Modular LED line light, 1000mm length, near field focusing, fan cooling, white
LTLNM-1000-N-D-FC-W	Modular LED line light, 1000mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1000-F-FC-W	Modular LED line light, 1000mm length, far field focusing, fan cooling, white
LTLNM-1000-F-D-FC-W	Modular LED line light, 1000mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1000-C-FC-W	Modular LED line light, 1000mm length, collimated, fan cooling, white
LTLNM-1000-C-D-FC-W	Modular LED line light, 1000mm length, collimated, diffuser, fan cooling, white
LTLNM-1200-N-FC-W	Modular LED line light, 1200mm length, near field focusing, fan cooling, white
LTLNM-1200-N-D-FC-W	Modular LED line light, 1200mm length, near field focusing, diffuser, fan cooling, white

LTLNM-1200-F-FC-W	Modular LED line light, 1200mm length, far field focusing, fan cooling, white
LTLNM-1200-F-D-FC-W	Modular LED line light, 1200mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1200-C-FC-W	Modular LED line light, 1200mm length, collimated, fan cooling, white
LTLNM-1200-C-D-FC-W	Modular LED line light, 1200mm length, collimated, diffuser, fan cooling, white
LTLNM-1400-N-FC-W	Modular LED line light, 1400mm length, near field focusing, fan cooling, white
LTLNM-1400-N-D-FC-W	Modular LED line light, 1400mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1400-F-FC-W	Modular LED line light, 1400mm length, far field focusing, fan cooling, white
LTLNM-1400-F-D-FC-W	Modular LED line light, 1400mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1400-C-FC-W	Modular LED line light, 1400mm length, collimated, fan cooling, white
LTLNM-1400-C-D-FC-W	Modular LED line light, 1400mm length, collimated, diffuser, fan cooling, white
LTLNM-1600-N-FC-W	Modular LED line light, 1600mm length, near field focusing, fan cooling, white
LTLNM-1600-N-D-FC-W	Modular LED line light, 1600mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1600-F-FC-W	Modular LED line light, 1600mm length, far field focusing, fan cooling, white
LTLNM-1600-F-D-FC-W	Modular LED line light, 1600mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1600-C-FC-W	Modular LED line light, 1600mm length, collimated, fan cooling, white
LTLNM-1600-C-D-FC-W	Modular LED line light, 1600mm length, collimated, diffuser, fan cooling, white
LTLNM-1800-N-FC-W	Modular LED line light, 1800mm length, near field focusing, fan cooling, white
LTLNM-1800-N-D-FC-W	Modular LED line light, 1800mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1800-F-FC-W	Modular LED line light, 1800mm length, far field focusing, fan cooling, white
LTLNM-1800-F-D-FC-W	Modular LED line light, 1800mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1800-C-FC-W	Modular LED line light, 1800mm length, collimated, fan cooling, white
LTLNM-1800-C-D-FC-W	Modular LED line light, 1800mm length, collimated, diffuser, fan cooling, white
LTLNM-2000-N-FC-W	Modular LED line light, 2000mm length, near field focusing, fan cooling, white
LTLNM-2000-N-D-FC-W	Modular LED line light, 2000mm length, near field focusing, diffuser, fan cooling, white
LTLNM-2000-F-FC-W	Modular LED line light, 2000mm length, far field focusing, fan cooling, white
LTLNM-2000-F-D-FC-W	Modular LED line light, 2000mm length, far field focusing, diffuser, fan cooling, white
LTLNM-2000-C-FC-W	Modular LED line light, 2000mm length, collimated, fan cooling, white
LTLNM-2000-C-D-FC-W	Modular LED line light, 2000mm length, collimated, diffuser, fan cooling, white



LTLNE series

High power enhanced LED line lights

LTLNE-300-N-PC-W	LED line light, direct, 300mm length, near field focusing, passive cooling, white
LTLNE-300-N-FC-W	LED line light, direct, 300mm length, near field focusing, fan cooling, white
LTLNE-300-N-D-PC-W	LED line light, direct, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-N-D-FC-W	LED line light, direct, 300mm length, near field focusing, diffuser, fan cooling, white
LTLNE-300-F-PC-W	LED line light, direct, 300mm length, far field focusing, passive cooling, white
LTLNE-300-F-FC-W	LED line light, direct, 300mm length, far field focusing, fan cooling, white
LTLNE-300-F-D-PC-W	LED line light, direct, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-F-D-FC-W	LED line light, direct, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-C-PC-W	LED line light, direct, 300mm length, collimated, passive cooling, white
LTLNE-300-C-FC-W	LED line light, direct, 300mm length, collimated, fan cooling, white
LTLNE-300-C-D-PC-W	LED line light, direct, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-C-D-FC-W	LED line light, direct, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-CX-N-PC-W	LED line light, coaxial, 300mm length, near field focusing, passive cooling, white
LTLNE-300-CX-N-FC-W	LED line light, coaxial, 300mm length, near field focusing, fan cooling, white
LTLNE-300-CX-N-D-PC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-CX-N-D-FC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, fan cooling, white

LTLNE-300-CX-F-PC-W	LED line light, coaxial, 300mm length, far field focusing, passive cooling, white
LTLNE-300-CX-F-FC-W	LED line light, coaxial, 300mm length, far field focusing, fan cooling, white
LTLNE-300-CX-F-D-PC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-CX-F-D-FC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-CX-C-PC-W	LED line light, coaxial, 300mm length, collimated, passive cooling, white
LTLNE-300-CX-C-FC-W	LED line light, coaxial, 300mm length, collimated, fan cooling, white
LTLNE-300-CX-C-D-PC-W	LED line light, coaxial, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-CX-C-D-FC-W	LED line light, coaxial, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-MR-N-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, passive cooling, white
LTLNE-300-MR-N-FC-W	LED line light, 45° mirror, 300mm length, near field focusing, fan cooling, white
LTLNE-300-MR-N-D-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, passive cooling, white
LTLNE-300-MR-F-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, fan cooling, white
LTLNE-300-MR-F-D-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-D-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-MR-C-PC-W	LED line light, 45° mirror, 300mm length, collimated, passive cooling, white
LTLNE-300-MR-C-FC-W	LED line light, 45° mirror, 300mm length, collimated, fan cooling, white
LTLNE-300-MR-C-D-PC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-MR-C-D-FC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, fan cooling, white