

MC4K200X-F

Macro lens for 4k line scan cameras, magnification 2.00x, F-mount

SPECIFICATIONS

Optical specifications

Focusing (1)		near	nominal	far
Magnification	(x)	2.042	2	1.955
Image circle Ø	(mm)	28.7		
Working distance (2)	(mm)	77.30	78.10	79.00
Focal length	(mm)	79.8		
f/# (wF/#) (3)		6.7 (20)		
Distortion typical (max) (4)	(%)	< 0.01 (0.03)		
Field depth (5)	(mm)	0.17	0.18	0.18
CTF @ 50 lp/mm	(%)	> 30		
Image side numerical aperture		0.025		
Object side numerical aperture		0.051		

Object field of view (mm x mm)

with IMX253/IMX304 17.6 mm diag w x h 14.16 x 10.37	6.95 x 5.09	7.10 x 5.20	7.26 x 5.32
with 2k x 10 µm detector 20.48	10.04	10.25	10.49
with IMX387 21.7 mm diag w x h 18.9 x 10.6	9.25 x 5.21	9.44 x 5.32	9.66 x 5.44
with APS-C IMX342 27.9 mm diagonal w x h 22.36 x 16.77	10.95 x 8.21	11.18 x 8.39	11.44 x 8.58
with 4k x 7 µm detector 28.67	14.05	14.35	14.68

Mechanical specifications

Length (6)	(mm)	218.5
Diameter	(mm)	64.0
Mass	(g)	755
Phase adjustment		Yes		
Mount		F

Last update: 2021-06-22

NOTES

- Maximum and minimum magnification changes when focusing.
- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- Working F-number: the real F-number of a lens in operating conditions.
- Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 7 µm.
- Measured from the front end of the mechanics to the camera flange.

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTBC series

Continuous LED backlight

LTBC054054-W

Continuous LED backlight, 54x54 illumination area, white



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.



LTBFC series

Continuous flat side-emitting LED backlights

[LTPVRG25X36-00-1-W-24V](#) Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, white, 24V

[LTPVRG25X36-00-1-R-24V](#) Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, red, 24V

[LTPVRG25X36-00-1-G-24V](#) Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, green, 24V

[LTPVRG25X36-00-1-B-24V](#) Flat side-emitting LED backlight, thin borders, 25X36 mm illumination area, blue, 24V



LTLAIC series (discontinued models)

Continuous LED low angle diffused ring lights

[LT2RZF050-60-2-W-24V](#) LED ring light, 2 LED rows, 50.8 mm outer diameter, 60°, white, 24V

[LT2RZF050-60-2-R-24V](#) LED ring light, 2 LED rows, 50.8 mm outer diameter, 60°, red, 24V

[LT2RZF050-60-2-G-24V](#) LED ring light, 2 LED rows, 50.8 mm outer diameter, 60°, green, 24V

[LT2RZF050-60-2-B-24V](#) LED ring light, 2 LED rows, 50.8 mm outer diameter, 60°, blue, 24V



LTRNDC series

Continuous LED direct ring lights

[LTZGK070-45-3-R-24V](#) LED ring light, 3 LED rows, outer diameter 70 mm, 45°, red, 24V

[LTZGK070-45-3-G-24V](#) LED ring light, 3 LED rows, outer diameter 70 mm, 45°, green, 24V

[LTZGK070-45-3-B-24V](#) LED ring light, 3 LED rows, outer diameter 70 mm, 45°, blue, 24V

[LTZGK070-45-3-W-24V](#) LED ring light, 3 LED rows, outer diameter 70 mm, 45°, white, 24V



LTLAIC series

Continuous LED low angle diffused ring lights

[LT3RZF050-60-1-W-24V](#) LED ring light, 1 LED row, 56.4 mm outer diameter, 60°, white, 24V

[LT3RZF050-60-1-R-24V](#) LED ring light, 1 LED row, 56.4 mm outer diameter, 60°, red, 24V

[LT3RZF050-60-1-G-24V](#) LED ring light, 1 LED row, 56.4 mm outer diameter, 60°, green, 24V

[LT3RZF050-60-1-B-24V](#) LED ring light, 1 LED row, 56.4 mm outer diameter, 60°, blue, 24V



LTLADC series

Continuous LED low angle direct ring lights

[LTZZO130-75-3-W-24V](#) LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, white, 24V

[LTZZO130-75-3-R-24V](#) LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, red, 24V

[LTZZO130-75-3-G-24V](#) LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, green, 24V

[LTZZO130-75-3-B-24V](#) LED low angle ring light, 3 LED rows, outer diameter 131 mm, 75°, blue, 24V



LTBRDC series

Continuous LED bar lights

[LTPPFL040-00-6-R-24V](#) LED bar light, 6 LED rows, 40X26.3 illumination area, red, 24V

[LTPPFL040-00-6-G-24V](#) LED bar light, 6 LED rows, 40X26.3 illumination area, green, 24V

[LTPPFL040-00-6-B-24V](#) LED bar light, 6 LED rows, 40X26.3 illumination area, blue, 24V

[LTPPFL040-00-6-W-24V](#) LED bar light, 6 LED rows, 40X26.3 illumination area, white, 24V



LTCXC series

Continuous LED coaxial lights

[LT2QOG025-00-X-W-24V](#) LED coaxial light, 25x25.6 mm light emitting area, white, 24V

[LT2QOG025-00-X-R-24V](#) LED coaxial light, 25x25.6 mm light emitting area, red, 24V

[LT2QOG025-00-X-G-24V](#) LED coaxial light, 25x25.6 mm light emitting area, green, 24V

[LT2QOG025-00-X-B-24V](#) LED coaxial light, 25x25.6 mm light emitting area, blue, 24V



LTLNC series

Continuous LED line lights

LTLNC100-W	LED line light 100 mm, white
LTLNC100-R	LED line light 100 mm, red
LTLNC100-G	LED line light 100 mm, green
LTLNC100-B	LED line light 100 mm, blue
LTLNC100-IR850	LED line light 100 mm, IR 850 nm
LTLNC150-W	LED line light 150 mm, white
LTLNC150-R	LED line light 150 mm, red
LTLNC150-G	LED line light 150 mm, green
LTLNC150-B	LED line light 150 mm, blue
LTLNC150-IR850	LED line light 150 mm, IR 850 nm
LTLNC200-W	LED line light 200 mm, white
LTLNC200-R	LED line light 200 mm, red
LTLNC200-G	LED line light 200 mm, green
LTLNC200-B	LED line light 200 mm, blue
LTLNC200-IR850	LED line light 200 mm, IR 850 nm
LTLNC300-W	LED line light 300 mm, white
LTLNC300-R	LED line light 300 mm, red
LTLNC300-G	LED line light 300 mm, green
LTLNC300-B	LED line light 300 mm, white
LTLNC300-IR850	LED line light 300 mm, IR 850 nm



LTLNM series

Flicker free high power focused modular LED line lights

LTLNM-0200-N-FC-W	Modular LED line light, 200mm length, near field focusing, fan cooling, white
LTLNM-0200-N-D-FC-W	Modular LED line light, 200mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0200-F-FC-W	Modular LED line light, 200mm length, far field focusing, fan cooling, white
LTLNM-0200-F-D-FC-W	Modular LED line light, 200mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0200-C-FC-W	Modular LED line light, 200mm length, collimated, fan cooling, white
LTLNM-0200-C-D-FC-W	Modular LED line light, 200mm length, collimated, diffuser, fan cooling, white
LTLNM-0400-N-FC-W	Modular LED line light, 400mm length, near field focusing, fan cooling, white
LTLNM-0400-N-D-FC-W	Modular LED line light, 400mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0400-F-FC-W	Modular LED line light, 400mm length, far field focusing, fan cooling, white
LTLNM-0400-F-D-FC-W	Modular LED line light, 400mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0400-C-FC-W	Modular LED line light, 400mm length, collimated, fan cooling, white
LTLNM-0400-C-D-FC-W	Modular LED line light, 400mm length, collimated, diffuser, fan cooling, white
LTLNM-0600-N-FC-W	Modular LED line light, 600mm length, near field focusing, fan cooling, white
LTLNM-0600-N-D-FC-W	Modular LED line light, 600mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0600-F-FC-W	Modular LED line light, 600mm length, far field focusing, fan cooling, white
LTLNM-0600-F-D-FC-W	Modular LED line light, 600mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0600-C-FC-W	Modular LED line light, 600mm length, collimated, fan cooling, white
LTLNM-0600-C-D-FC-W	Modular LED line light, 600mm length, collimated, diffuser, fan cooling, white
LTLNM-0800-N-FC-W	Modular LED line light, 800mm length, near field focusing, fan cooling, white
LTLNM-0800-N-D-FC-W	Modular LED line light, 800mm length, near field focusing, diffuser, fan cooling, white
LTLNM-0800-F-FC-W	Modular LED line light, 800mm length, far field focusing, fan cooling, white
LTLNM-0800-F-D-FC-W	Modular LED line light, 800mm length, far field focusing, diffuser, fan cooling, white
LTLNM-0800-C-FC-W	Modular LED line light, 800mm length, collimated, fan cooling, white
LTLNM-0800-C-D-FC-W	Modular LED line light, 800mm length, collimated, diffuser, fan cooling, white
LTLNM-1000-N-FC-W	Modular LED line light, 1000mm length, near field focusing, fan cooling, white
LTLNM-1000-N-D-FC-W	Modular LED line light, 1000mm length, near field focusing, diffuser, fan cooling, white

LTLNM-1000-F-FC-W	Modular LED line light, 1000mm length, far field focusing, fan cooling, white
LTLNM-1000-F-D-FC-W	Modular LED line light, 1000mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1000-C-FC-W	Modular LED line light, 1000mm length, collimated, fan cooling, white
LTLNM-1000-C-D-FC-W	Modular LED line light, 1000mm length, collimated, diffuser, fan cooling, white
LTLNM-1200-N-FC-W	Modular LED line light, 1200mm length, near field focusing, fan cooling, white
LTLNM-1200-N-D-FC-W	Modular LED line light, 1200mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1200-F-FC-W	Modular LED line light, 1200mm length, far field focusing, fan cooling, white
LTLNM-1200-F-D-FC-W	Modular LED line light, 1200mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1200-C-FC-W	Modular LED line light, 1200mm length, collimated, fan cooling, white
LTLNM-1200-C-D-FC-W	Modular LED line light, 1200mm length, collimated, diffuser, fan cooling, white
LTLNM-1400-N-FC-W	Modular LED line light, 1400mm length, near field focusing, fan cooling, white
LTLNM-1400-N-D-FC-W	Modular LED line light, 1400mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1400-F-FC-W	Modular LED line light, 1400mm length, far field focusing, fan cooling, white
LTLNM-1400-F-D-FC-W	Modular LED line light, 1400mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1400-C-FC-W	Modular LED line light, 1400mm length, collimated, fan cooling, white
LTLNM-1400-C-D-FC-W	Modular LED line light, 1400mm length, collimated, diffuser, fan cooling, white
LTLNM-1600-N-FC-W	Modular LED line light, 1600mm length, near field focusing, fan cooling, white
LTLNM-1600-N-D-FC-W	Modular LED line light, 1600mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1600-F-FC-W	Modular LED line light, 1600mm length, far field focusing, fan cooling, white
LTLNM-1600-F-D-FC-W	Modular LED line light, 1600mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1600-C-FC-W	Modular LED line light, 1600mm length, collimated, fan cooling, white
LTLNM-1600-C-D-FC-W	Modular LED line light, 1600mm length, collimated, diffuser, fan cooling, white
LTLNM-1800-N-FC-W	Modular LED line light, 1800mm length, near field focusing, fan cooling, white
LTLNM-1800-N-D-FC-W	Modular LED line light, 1800mm length, near field focusing, diffuser, fan cooling, white
LTLNM-1800-F-FC-W	Modular LED line light, 1800mm length, far field focusing, fan cooling, white
LTLNM-1800-F-D-FC-W	Modular LED line light, 1800mm length, far field focusing, diffuser, fan cooling, white
LTLNM-1800-C-FC-W	Modular LED line light, 1800mm length, collimated, fan cooling, white
LTLNM-1800-C-D-FC-W	Modular LED line light, 1800mm length, collimated, diffuser, fan cooling, white
LTLNM-2000-N-FC-W	Modular LED line light, 2000mm length, near field focusing, fan cooling, white
LTLNM-2000-N-D-FC-W	Modular LED line light, 2000mm length, near field focusing, diffuser, fan cooling, white
LTLNM-2000-F-FC-W	Modular LED line light, 2000mm length, far field focusing, fan cooling, white
LTLNM-2000-F-D-FC-W	Modular LED line light, 2000mm length, far field focusing, diffuser, fan cooling, white
LTLNM-2000-C-FC-W	Modular LED line light, 2000mm length, collimated, fan cooling, white
LTLNM-2000-C-D-FC-W	Modular LED line light, 2000mm length, collimated, diffuser, fan cooling, white



LTLNE series

High power enhanced LED line lights

LTLNE-300-N-PC-W	LED line light, direct, 300mm length, near field focusing, passive cooling, white
LTLNE-300-N-FC-W	LED line light, direct, 300mm length, near field focusing, fan cooling, white
LTLNE-300-N-D-PC-W	LED line light, direct, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-N-D-FC-W	LED line light, direct, 300mm length, near field focusing, diffuser, fan cooling, white
LTLNE-300-F-PC-W	LED line light, direct, 300mm length, far field focusing, passive cooling, white
LTLNE-300-F-FC-W	LED line light, direct, 300mm length, far field focusing, fan cooling, white
LTLNE-300-F-D-PC-W	LED line light, direct, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-F-D-FC-W	LED line light, direct, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-C-PC-W	LED line light, direct, 300mm length, collimated, passive cooling, white
LTLNE-300-C-FC-W	LED line light, direct, 300mm length, collimated, fan cooling, white

LTLNE-300-C-D-PC-W	LED line light, direct, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-C-D-FC-W	LED line light, direct, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-CX-N-PC-W	LED line light, coaxial, 300mm length, near field focusing, passive cooling, white
LTLNE-300-CX-N-FC-W	LED line light, coaxial, 300mm length, near field focusing, fan cooling, white
LTLNE-300-CX-N-D-PC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-CX-N-D-FC-W	LED line light, coaxial, 300mm length, near field focusing, diffuser, fan cooling, white
LTLNE-300-CX-F-PC-W	LED line light, coaxial, 300mm length, far field focusing, passive cooling, white
LTLNE-300-CX-F-FC-W	LED line light, coaxial, 300mm length, far field focusing, fan cooling, white
LTLNE-300-CX-F-D-PC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-CX-F-D-FC-W	LED line light, coaxial, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-CX-C-PC-W	LED line light, coaxial, 300mm length, collimated, passive cooling, white
LTLNE-300-CX-C-FC-W	LED line light, coaxial, 300mm length, collimated, fan cooling, white
LTLNE-300-CX-C-D-PC-W	LED line light, coaxial, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-CX-C-D-FC-W	LED line light, coaxial, 300mm length, collimated, diffuser, fan cooling, white
LTLNE-300-MR-N-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, passive cooling, white
LTLNE-300-MR-N-FC-W	LED line light, 45° mirror, 300mm length, near field focusing, fan cooling, white
LTLNE-300-MR-N-D-PC-W	LED line light, 45° mirror, 300mm length, near field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, passive cooling, white
LTLNE-300-MR-F-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, fan cooling, white
LTLNE-300-MR-F-D-PC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, passive cooling, white
LTLNE-300-MR-F-D-FC-W	LED line light, 45° mirror, 300mm length, far field focusing, diffuser, fan cooling, white
LTLNE-300-MR-C-PC-W	LED line light, 45° mirror, 300mm length, collimated, passive cooling, white
LTLNE-300-MR-C-FC-W	LED line light, 45° mirror, 300mm length, collimated, fan cooling, white
LTLNE-300-MR-C-D-PC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, passive cooling, white
LTLNE-300-MR-C-D-FC-W	LED line light, 45° mirror, 300mm length, collimated, diffuser, fan cooling, white