

PC13030HP

Pericentric lens for 1/3" detectors

SPECIFICATIONS

Detector type		1/3"
Image circle Ø	(mm)	3.6
Field of view (diameter x height)		
Minimum	(mm x mm)	20 x 60
Typical	(mm x mm)	30 x 30
Maximum	(mm x mm)	60 x 20
Optical specifications		
Wavelength range	(nm)	450 .. 650
Working distance	(mm)	20 .. 80
CTF @ 50 lp/mm	(%)	> 30
F/#		4-16
Mechanical specifications		
Diameter	(mm)	197
Length	(mm)	448
Mass	(g)	6800
Mount		C

Last update: 2017-12-15

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® **technical support** department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTRNOB series

LED ring illuminators - oblique type

LTRN245R25	Ring LED illuminator, inner diameter 158.5 mm, oblique type, red 630 nm
LTRN245G25	Ring LED illuminator, inner diameter 158.5 mm, oblique type, green 525 nm
LTRN245B25	Ring LED illuminator, inner diameter 158.5 mm, oblique type, blue 470 nm
LTRN245W25	Ring LED illuminator, inner diameter 158.5 mm, oblique type, white



LTRNOBHP series

High power LED ring illuminators, oblique type

LTRNHP245R25	High power LED ring illuminators, oblique type, inner diam. 157mm, red, 625 nm
LTRNHP245G25	High power LED ring illuminators, oblique type, inner diam. 157mm, green, 525 nm
LTRNHP245B25	High power LED ring illuminators, oblique type, inner diam. 157mm, blue, 475 nm
LTRNHP245W25	High power LED ring illuminators, oblique type, inner diam. 157mm, white, 6200 k



OI series

Replacement ocular lenses

OIHP13030	Replacement ocular lens for PC13030HP optics
-----------	--



COE-G series

GeniCam® PoE cameras



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

COE-003-M-POE-020-IR-C	Area Scan camera RJ33B4AD0DT, CCD, Global shutter, 640 x 480, 0.3 MP, 7.4 pix, 1/3", Gray, 200 fps, GigE, POE, C - mount, Glass filter
COE-003-C-POE-020-IR-C	Area Scan camera RJ33B4AD0DT, CCD, Global shutter, 640 x 480, 0.3 MP, 7.4 pix, 1/3", Color, 200 fps, GigE, POE, C - mount, Infrared cut filter
COE-012-M-POE-020-IR-C	Area Scan camera RJ33J4CA3DE, CCD, Global shutter, 1280 x 960, 1.2 MP, 3.75 pix, 1/3", Gray, 30 fps, GigE, POE, C - mount, Glass filter
COE-012-C-POE-020-IR-C	Area Scan camera RJ33J4CA3DE, CCD, Global shutter, 1280 x 960, 1.2 MP, 3.75 pix, 1/3", Color, 30 fps, GigE, POE, C - mount, Infrared cut filter
COE-050-M-POE-023-IR-C	Area Scan camera MT9P031, CMOS, Rolling shutter, 2592 x 1944, 5 MP, 2.2 pix, 1/2.5", Gray, 14 fps, GigE, POE, C - mount, Glass filter
COE-106-M-POE-031-IR-C-2	Area Scan camera MT9J003, CMOS, Rolling shutter, 3840 x 2748, 10.6 MP, 1.67 pix, 1/2.3", Gray, 11 fps, GigE, POE, C - mount, Glass filter
COE-106-C-POE-031-IR-C	Area Scan camera MT9J003, CMOS, Global shutter, 3840 x 2748, 10.6 MP, 1.67 pix, 1/2.3", Color, 7 fps, GigE, POE, C - mount, Infrared cut filter



COE-U series

USB 3.0 GenICam® cameras

COE-016-M-USB-021-IR-C	Area Scan camera IMX273, CMOS, Global shutter, 1440 x 1080, 1.6 MP, 3.45 pix, 1/2.9", Gray, 165 fps, USB 3.0, C - mount, Glass filter
COE-016-C-USB-021-IR-C	Area Scan camera IMX273, CMOS, Global shutter, 1440 x 1080, 1.6 MP, 3.45 pix, 1/2.9", Color, 165 fps, USB 3.0, C - mount, Infrared cut filter
COE-050-C-USB-023-IR-C	Area Scan camera AR0521, CMOS, Rolling shutter, 2592 x 1944, 5 MP, 2.2 pix, 1/2.5", Color, 31 fps, USB 3.0, C - mount, Infrared cut filter



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2004	USB3 vision camera with Sony Pregius CMOS sensor IMX287
RT-mvBF3-2016	USB3 vision camera with Sony Pregius CMOS sensor IMX273



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X100f	Camera with interface GigE (1GB/s), sensor size 1/2.9", mpixel 0.4, resolution 728 x 544, sensor name IMX287, sensor type CMOS
RT-mvBC-X102f	Camera with interface GigE (1GB/s), sensor size 1/2.9", mpixel 1.58, resolution 1456 x 1088, sensor name IMX273, sensor type CMOS
RT-mvBC-XD102f	Camera with interface Dual GigE (2GB/s), sensor size 1/2.9", mpixel 1.58, resolution 1456 x 1088, sensor name IMX273, sensor type CMOS
RT-mvBC-X105	Camera with interface GigE (1GB/s), sensor size 1/2.5", mpixel 5.04, resolution 2592 x 1944, sensor name MT9P031, sensor type CMOS
RT-mvBC-X1010	Camera with interface GigE (1GB/s), sensor size 1/2.3", mpixel 10.66, resolution 3856 x 2764, sensor name MT9J003, sensor type CMOS



Accessories

Accessories and add-ons to make the most of Opto Engineering lenses.

RT-mvBC-X104iC	CMOS camera GIGE, 2064 x 1544 color, 1/1.8", 37 Hz, IR cut, C-mount, I/O
RT-mvBC-X105bC	CMOS camera GIGE, 2464 x 2056 Colour sensor, 2/3", 23.5 Hz, IR cut, C-mount, I/O