

# PCMP012

Micro Polyview optics for 1/2", C-mount

## SPECIFICATIONS

Detector type		1/2"
Image circle Ø	(mm)	4.8
Max object inspection height		
With 2.5 mm diameter	(mm)	6
With 5.0 mm diameter	(mm)	4.5
With 7.5 mm diameter	(mm)	3
With 10.0 mm diameter	(mm)	1
Optical specifications		
Wavelength range	(nm)	450...650
Working distance	(mm)	1.5...5
CTF @ 50 lp/mm	(%)	> 40
wF/# 1		8
Mechanical specifications		
Diameter	(mm)	119
Length	(mm)	262
Mass	(g)	980
Mount		C
Electrical specifications		
Illuminator voltage	(V, DC)	24
Illuminator power consumption	(W)	18

Last update: 2017-12-15

## NOTES

- Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- F/# = F-number, wF/# = working F-number, the real F-number of a lens when used as a macro.

## COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



### Accessories

Accessories and add-ons to make the most of Opto Engineering lenses.

PCMPMIRR	Replacement mirror array for PCMP series
RT-mvBC-X104iC	CMOS camera GIGE, 2064 x 1544 color, 1/1.8", 37 Hz, IR cut, C-mount, I/O
RT-mvBC-X105bC	CMOS camera GIGE, 2464 x 2056 Colour sensor, 2/3", 23.5 Hz, IR cut, C-mount, I/O



### COE-G series

GenICam® PoE cameras

COE-013-M-POE-030-IR-C	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", Gray, 90 fps, GigE, POE, C - mount, Glass filter
COE-013-C-POE-030-IR-C	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", Color, 90 fps, GigE, POE, C - mount, Infrared cut filter
COE-032-M-POE-040-IR-C	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", Gray, 37.5 fps, GigE, POE, C - mount, Glass filter



All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only.

<a href="#">COE-032-C-POE-040-IR-C</a>	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", Color, 37.5 fps, GigE, POE, C - mount, Infrared cut filter
<a href="#">COE-063-M-POE-040-IR-C-B</a>	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Gray, 17 fps, GigE, POE, C - mount, Glass filter
<a href="#">COE-063-C-POE-040-IR-C</a>	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Color, 17 fps, GigE, POE, C - mount, Infrared cut filter
<a href="#">COE-122-M-POE-041-IR-C</a>	Area Scan camera IMX226, CMOS, Rolling shutter, 4024 x 3036, 12.2 MP, 1.85 pix, 1/1.7", Gray, 9.6 fps, GigE, POE, C - mount, Glass filter
<a href="#">COE-122-C-POE-041-IR-C</a>	Area Scan camera IMX226, CMOS, Rolling shutter, 4024 x 3036, 12.2 MP, 1.85 pix, 1/1.7", Color, 9.6 fps, GigE, POE, C - mount, Infrared cut filter



#### COE-U series

USB 3.0 GenICam® cameras

<a href="#">COE-013-M-USB-030-IR-C</a>	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", Gray, 170 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-013-C-USB-030-IR-C</a>	Area Scan camera PYTHON 1300, CMOS, Global shutter, 1280 x 1024, 1.3 MP, 4.8 pix, 1/2", Color, 90 fps, USB 3.0, C - mount, Infrared cut filter
<a href="#">COE-063-M-USB-040-IR-C</a>	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Gray, 42 fps, USB 3.0, C - mount, Glass filter
<a href="#">COE-063-C-USB-040-IR-C</a>	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Color, 42 fps, USB 3.0, C - mount, Infrared cut filter



#### mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

<a href="#">RT-mvBF3-2032a</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX265
<a href="#">RT-mvBF3-2032</a>	USB3 Vision camera with Sony Pregius CMOS sensor IMX252
<a href="#">RT-mvBF3-2064</a>	USB3 vision camera with Sony Pregius CMOS sensor IMX178



#### mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

<a href="#">RT-mvBC-X104i</a>	Camera with interface GigE (1GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX265, sensor type CMOS
<a href="#">RT-mvBC-XD104h</a>	Camera with interface Dual GigE (2GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX252, sensor type CMOS