

TCBENCH009

Telecentric optical bench, magnification 1.00

SPECIFICATIONS

Object field of view

with 1/3" detector (4.8 x 3.6 mm)	(mm x mm)	4.80 x 3.60
with 1/2.5" detector (5.70 x 4.28 mm)	(mm x mm)	5.70 x 4.28
with 1/2" detector (6.4 x 4.8 mm)	(mm x mm)	6.40 x 4.80
with 1/1.8" detector (7.13 x 5.37 mm)	(mm x mm)	7.13 x 5.37
with 2/3" detector (8.8 x 6.6 mm)	(mm x mm)	8.44 x 7.06

Optical specifications

Magnification	(x)	1.000
Light color, peak wavelength		green, 520 nm
Working distance (1)		62,2
Working f/#		11
Optical Accuracy (2)	(μ m)	< 5
Optical Accuracy (3)	(%)	< 0.06%
Field depth (4)	(mm)	0.9
CTF @ 70 lp/mm	(%)	> 35

Dimensions

Length	(mm)	292
Width	(mm)	56.0
Height	(mm)	78.5
Mass	(g)	950
Mount		C

Phase adjustment (5)

NOTES

1. Working distance: distance between the front end of the lens mechanics and the object. Set this distance within +/-3% of the nominal value for maximum resolution
2. Maximum measurement error without software calibration; standard image correction libraries yield close to zero measurement error.
3. Maximum measurement error without software calibration; standard image correction libraries yield close to zero measurement error.
4. At the borders of the field depth the image can be still used for measurement but, to get a very sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5.5 μ m.
5. Indicates the availability of an integrated camera phase adjustment feature. If missing, it can be supplied upon request (except for TCBENCH009).

COMPATIBLE PRODUCTS

Despite the efforts made to generate an error-free compatibility list, we always recommend to consult the Opto Engineering® technical support department before purchasing a compatible product. Opto Engineering® shall not be liable for any damage or malfunctioning caused by the incorrect selection of a compatible product.



LTSCHP series


High-performance replacement LED modules

LTSCHP1W-G	Replacement LED module, green
LTSCHP1W-GZ	Replacement LED module with diffuser, green



PS series

Power supplies





LTIC series

Light intensity controllers

LTICOBUL1000CH1-24VUSTB	24VDC analog lighting controller 1 channel, UK power cord, Illumination cable, side A 5M 3 way male connector, side B terminal blocks connector, 24V - 3m
LTICOBUL1000CH1-24VEUTB	24VDC analog lighting controller 1 channel, UK power cord, Illumination cable, side A 5M 3 way male connector, side B terminal blocks connector, 24V - 3m
LTICOBUL1000CH1-24VUKTB	24VDC analog lighting controller 1 channel, UK power cord, Illumination cable, side A 5M 3 way male connector, side B terminal blocks connector, 24V - 3m



COE-G series

GeniCam® PoE cameras

COE-032-M-POE-040-IR-C	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", Gray, 37.5 fps, GigE, POE, C - mount, Glass filter
COE-032-C-POE-040-IR-C	Area Scan camera IMX265, CMOS, Global shutter, 2048 x 1536, 3.1 MP, 3.45 pix, 1/1.8", Color, 37.5 fps, GigE, POE, C - mount, Infrared cut filter
COE-063-M-POE-040-IR-C-B	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Gray, 17 fps, GigE, POE, C - mount, Glass filter
COE-063-C-POE-040-IR-C	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Color, 17 fps, GigE, POE, C - mount, Infrared cut filter
COE-122-M-POE-041-IR-C	Area Scan camera IMX226, CMOS, Rolling shutter, 4024 x 3036, 12.2 MP, 1.85 pix, 1/1.7", Gray, 9.6 fps, GigE, POE, C - mount, Glass filter
COE-122-C-POE-041-IR-C	Area Scan camera IMX226, CMOS, Rolling shutter, 4024 x 3036, 12.2 MP, 1.85 pix, 1/1.7", Color, 9.6 fps, GigE, POE, C - mount, Infrared cut filter
COE-023-M-POE-050-IR-C	Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", Gray, 51 fps, GigE, POE, C - mount, Glass filter
COE-023-C-POE-050-IR-C	Area Scan camera PYTHON 2000, CMOS, Global shutter, 1920 x 1200, 2.3 MP, 4.8 pix, 2/3", Color, 51 fps, GigE, POE, C - mount, Infrared cut filter
COE-050-M-POE-050-IR-C	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", Gray, 23.5 fps, GigE, POE, C - mount, Glass filter
COE-050-C-POE-050-IR-C	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", Color, 23.5 fps, GigE, POE, C - mount, Infrared cut filter



COE-U series

USB 3.0 GeniCam® cameras

COE-063-M-USB-040-IR-C	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Gray, 42 fps, USB 3.0, C - mount, Glass filter
COE-063-C-USB-040-IR-C	Area Scan camera IMX178, CMOS, Rolling shutter, 3072 x 2048, 6.3 MP, 2.4 pix, 1/1.8", Color, 42 fps, USB 3.0, C - mount, Infrared cut filter
COE-050-M-USB-050-IR-C	Area Scan camera IMX264, CMOS, Global shutter, 2448 x 2048, 5 MP, 3.45 pix, 2/3", Gray, 35 fps, USB 3.0, C - mount, Glass filter



mvBlueFOX3-2 series

USB3 vision camera with Sony Pregius CMOS sensors

RT-mvBF3-2032a	USB3 Vision camera with Sony Pregius CMOS sensor IMX265
RT-mvBF3-2032	USB3 Vision camera with Sony Pregius CMOS sensor IMX252
RT-mvBF3-2064	Usb3 vision camera with sony pregius cmos sensor imx178
RT-mvBF3-2051a	USB3 Vision camera with Sony Pregius CMOS sensor IMX264
RT-mvBF3-2051	USB3 Vision camera with Sony Pregius CMOS sensor IMX250



mvBlueCOUGAR series

GigE & Dual GigE Vision cameras

RT-mvBC-X104i	Camera with interface GigE (1GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX265, sensor type CMOS
RT-mvBC-XD104h	Camera with interface Dual GigE (2GB/s), sensor size 1/1.8", mpixel 3.19, resolution 2064 x 1544, sensor name IMX252, sensor type CMOS

[RT-mvBC-X105b](#) Camera with interface GigE (1GB/s), sensor size 2/3", mpixel 5.07, resolution 2464 x 2056, sensor name IMX264, sensor type CMOS

[RT-mvBC-XD105a](#) Camera with interface Dual GigE (2GB/s), sensor size 2/3", mpixel 5.01, resolution 2448 x 2048, sensor name IMX250, sensor type CMOS



Accessories

Accessories and add-ons to make the most of Opto Engineering lenses.

[RT-mvBC-X104iC](#) CMOS camera GIGE, 2064 x 1544 color, 1/1.8", 37 Hz, IR cut, C-mount, I/O

[RT-mvBC-X105bC](#) CMOS camera GIGE, 2464 x 2056 Colour sensor, 2/3", 23.5 Hz, IR cut, C-mount, I/O
