



DETTAGLIO A
SCALA 4 : 1

Pinout :

- +VC: +24 V for continuous illumination. Max current 150 mA
- +VP: +24 V for pulsed illumination. Max current 2800 mA. Max duty cycle 1%. Max Ton 1 ms
- GND: ground

Material		N.A.		Mass		84,495 g		Scale		2:1					
Surface treatment		N.A.		Part No.		CO29785									
Geometrical tolerance (ISO 2768-2)								Class	K	Undimensioned bevels		0,5x45°			
Linear tolerance (ISO 2768-2)								Class	m	Undimensioned radii		R 0.5			
0.5 ±3	>3÷ 6	>6÷ 30	>30÷ 120	>120 ±400	>400÷ 1000	>1000 ±2000	>2000 ±4000	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2
				Date		Name		Drawing No.		Sheet					
Designed				23/01/2020		Rodella		DP 29785-B		1/1					
Drawn				17/02/2020		Rodella		<i>Secret and confidential - All rights reserved - No copy, dissemination or circulation is allowed unless specifically authorized in writing by OPTO ENGINEERING S.r.l. - Any violation shall be legally prosecuted.</i>							
Checked				27/02/2020		Bertolucci									
OPTO ENGINEERING S.r.l. - Mantova Italy - Tel. +39 0376 699111 - www.opto-engineering.com															

all dimensions are in mm