

# OUTLINE

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES AS FOLLOWS

DEC. .XXX ± .005  
 DEC. .XX ± .010  
 FRACT. ± 1/64  
 ANGLES ± 30'  
 CONCENTRICITY .003 TIR

BREAK ALL SHARP EDGES .005 MIN. .010 MAX.

MAX. SURF. ROUGHNESS:  $\sqrt{32}$

P/N SUFFIX DEFINITION

- 1 CONVERSION COATING
- 2 PAINTING
- 3 MARKING
- R REWORK

SCALE: 1:1

DR: R. PODLENA



CH: P. BONAFEDE

APP:

DATE DR: 5/15/2002

DO NOT SCALE DRAWING

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR



RIGHT ANGLE 1.33X PRECISE EYE ADAPTER

SIZE

A

1-62539\_OL

SHEET 1 OF 1

REV

A

CHAMFER ALL THREADS 30° TO ROOT DIAMETER