





# OUTLINE

USED ON:

|   |   |   |  |   |                          |  |
|---|---|---|--|---|--------------------------|--|
| <p><b>MATERIAL:</b></p> <p>Aluminum-6061</p>    | <p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES</p>  | <p><u>P/N SUFFIX DEFINITION</u></p> <p>-1 CONVERSION COATING<br/>-2 PAINTING<br/>-3 MARKING<br/>-R REWORK</p> | <p>THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR</p>   |  |                          |  |
| <p><b>FINISH:</b></p>                           | <p>TOLERANCES AS FOLLOWS</p> <p>DEC. .XXX ± .005<br/>DEC. .XX ± .010<br/>FRACT. ± 1/64<br/>ANGLES ± 30'<br/>CONCENTRICITY .003 TIR</p> <p>BREAK ALL SHARP EDGES .005 MIN. .010 MAX.</p> | <p>SCALE: 2:1</p>   | <p>0.0 inch 1.0</p>  <p>0.0 mm 25.0</p>  |   |                          | <p>Z6/MITUTOYO OBJECTIVE COUPLER</p>         |
| <p>CHAMFER ALL THREADS 30° TO ROOT DIAMETER</p> | <p>MAX. SURF. ROUGHNESS: <math>\sqrt{32}</math></p>   | <p>DATE DR: 7/24/2001</p> <p>DO NOT SCALE DRAWING</p>   |  |  | <p>SIZE<br/><b>A</b></p> | <p><b>3-60160_OL</b></p> <p>SHEET 1 OF 1</p> |